

`templateName`, as follows:

```
<body>
<div class="container">
  <ul>
    {{#each lines}}
    {{> line}}
    {{/each}}
  </ul>
</div>
</body>
<template name="helperDemo">
  <li>{{line}}</li>
</template>
```

helperdemo.js: The following helper passes data to the template. The helper named 'lines' returns an array to the template, where we loop over the array and display each line in an unordered list using html tags.

```
Template.body.helpers({
  lines: [
    { line: "This is line 1" },
    { line: "This is line 2" },
    { line: "This is line 3" }
  ]
});
```

Collections

Collections are nothing but databases. By default, Meteor comes with MongoDB, which is automatically installed and doesn't require any configuration. This database can be accessed on the server as well as the client side.

To create a collection, just add the following line in a js file:

```
MyDb = new Mongo.Collection("testDb");
```

This database can be viewed both from the server and the client. On the server side, the database operations can be performed on the Meteor Mongo console and on the client side, these can be done on the browser console. In order to insert data into the database, open a new terminal tab, go to your *app* directory and type the following command:

```
meteor mongo
```

This opens a console in your app's local development database. At the prompt, type the following command:

```
db.testDb.insert({ text: "Hello world!", createdAt: new Date() });
```

The same can be done with the browser console or through the JavaScript file. Now this database is automatically

made available to both client and server. To view the inserted elements, enter the following command:

```
db.testDb.find();
```

Events

In Meteor, events are associated with templates. Events are attached to templates in the form *Template.templateName.events*, where *events* is a keyword. The following code attaches a click event to a template.

events.html

```
<head>
<title>Meteor events</title>
</head>
<body>
  <h1>Welcome to Meteor!</h1>
  {{> meteorEvents}}
</body>
<template name="meteorEvents">
  <button>Click Me</button>
</template>
```

events.js

```
Template.meteorEvents.events({
  'click button': function () {
    console.log("You have clicked a button")
  }
});
```



Figure 3: Defining Views with templates



Figure 4: Inserting values into MongoDB



Figure 5: Fetching values from MongoDB