

Here, use *r* or *read* to load *myanotherfile.txt* just below the text of *myfile.txt*.

If you wish to place the *myanotherfile.txt*'s contents at the fifth line of *myfile.txt*, open the file in VIM, as follows:

```
# vi myfile.txt
```

Then, use the following command:

```
:4r myanotherfile.txt
```

...so that the contents of *myanotherfile.txt* are placed immediately after the fourth line (in other words, on the fifth line as we wanted).

You can do this even without opening the *myfile.txt*.

The following command illustrates how to insert *myanotherfile.txt*'s contents on *myfile.txt*:

```
# sed -i 'r myanotherfile.txt' myfile.txt
```

Now, *myanotherfile.txt*'s contents on *myfile.txt* are at the second line.

If you wish to place this on the fifth line, then use the following command:

```
# sed -i '4r myanotherfile.txt' myfile.txt
```

If you would like to insert a word on a particular line, you can run the following command:

```
# sed -i '4a NEW LINE ADDED' myfile.txt
```

You can see 'NEW LINE ADDED' on *myfile.txt* at the fifth line.

—*Ranjithkumar T, ranjith.stc@gmail.com*

Turn on computers using Linux commands

Any computer or server can be remotely turned on using Wake-on-LAN. To use this, we need to configure the Wake-on-LAN feature in the BIOS of the computer that needs to be turned on. We also need the software to send the 'magic packet' on the remote computer.

Install *etherwake* using the package manager on the computer that needs to send the 'magic packet' as follows:

```
$ sudo aptitude install etherwake
```

Now, send the Wake-on-LAN packet using the following command:

```
$ etherwake <MACAddress of the computer to be turned on>
```

You can check if the computer that needs to be turned on supports Wake-on-LAN by using the following command:

```
$ ethtool eth0
```

—*Ajinkya Jiman, ajinkya.jiman@gmail.com*

Finding out the process ID

Often, you will want to know the process ID but not be able to find it because the process is running in the background. So simply type in the following command at your terminal:

```
$pgrep Process_name
```

Example:

```
$pgrep firefox
```

The output of the above command will give the ID.

—*Dilip Pandit, panditdilip@gmail.com*

Restrict the use of old passwords

To configure the system to remember the last five passwords and prohibit their reuse, modify the *pam_unix* so line in the password phase of the */etc/pam.d/system-auth* file, ensuring that it includes "remember=5".

The following line is already present in the */etc/pam.d/system-auth* file but without the 'remember' option, so just add it and set it to '5' as follows:

```
password sufficient pam_unix.so sha512 shadow nullok try_
first_pass use_authok remember=5
```

The value of the "remember" parameter is the number of old passwords you want to store for a user.

Please note that the last five passwords for each user are saved in the */etc/security/opasswd* file. This prevents people from using any one of the five previously used passwords.

—*Krishna Murthy Thimmaiah, gtk321@rediffmail.com*

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.