

```
INFO: Restoring MyRemoteFile20150808.ttgz
INFO: Downloading...
INFO: Job ArchiveRetrieval: InProgress
```

You can delete a backup as follows:

```
$ bakthat delete MyBackup.tgz.enc
INFO: Deleting MyBackup.tgz.enc
$ bakthat delete -f MyRemoteFile
INFO: Deleting MyRemoteFile201502274848.ttgz.enc
```

You can view backup information by using the following code:

```
$ bakthat info
INFO: Last backup date: <Backup TimeStamp> (1 versions)
```

Attic, a de-duplicating backup tool

Attic is a cross-platform backup tool for Linux distributions, Mac OS X and FreeBSD. This tool is developed and used for the secured and de-duplicated storage of data so that only the modified files and changes can be stored rather than the full backup, every time.

Attic is developed in the Python programming language in association with implementations of Cython and C.

Its features include:

- De-duplication/non-redundant backup
- Encryption of data
- Backup on remote hosts
- Backup with *Mount* as file systems
- Backup validation, verification and restore

Attic installation: To install Attic, Python 3.2 or later is required. To install Attic using Pip, use the following command:

```
$ pip3 install Attic
```

To install from source tarballs, use the following code:

```
$ curl -O https://pypi.python.org/packages/source/A/Attic/Attic-0.16.tar.gz
$ tar -xvzf Attic-0.16.tar.gz
$ cd Attic-0.16
$ python setup.py install
```

To install from git, use the following commands:

```
$ git clone https://www.github.com/jborg/attic.git
$ cd attic
$ python setup.py install
```

Creating the repository: First of all, a new backup repository is initialised, as follows:

```
$ attic init /MyDirectory/my-repository.attic
```

After initializing, the creation of repository is done

```
$ attic create /MyDirectory /my-repository.
attic::SundayEvening ~/MyDocuments
$ attic create --stats / MyDirectory /my-repository.
attic::MondayEvening ~/ MyDocuments
Archive name: MondayEvening
Archive fingerprint: 178a5e3f9b0e792e91ce98673b0f4bfe45213d
9248cb7879f3fbf3a8e679808a
Start time: Mon Jul 27 12:00:10 2015
End time: Mon Jul 27 12:00:10 2015
Number of files: 1000
```

	Original size	Compressed size	Deduplicated size
This archive:	97.36 MB	66.28 MB	298.17 kB
All archives:	82.12 MB	80.42 MB	38.29 MB

Another example of code for initialising the backup repository and creating a backup archive is shown below:

```
$ attic init /MyUSBDrive/MyBackup.attic
$ attic create -v / MyUSBDrive / MyBackup.attic::documents
~/AllDocuments
```

Restore the *MondayEvening* archive, as follows:

```
$ attic extract /MyDirectory/ MyBackup.attic::MondayEvening
```

Recover disk space by manually deleting the *MondayEvening* archive, using the following command:

```
$ attic delete / MyDirectory /MyBackup.attic:: MondayEvening
```

Initialise and create a remote repository, as follows:

```
$ attic init user@hostname:mybackuprepo.attic
```

OR

```
$ attic init user@hostname:repository.attic
```

OR

```
$ attic init ssh://user@hostname:port/repository.attic
```

In case Attic cannot be installed on a remote host, the latter can be used for storing the repository by using *mount* with the remote file system using *sshfs*, as shown below:

```
$ sshfs username@hostname:/PathToDirectory/ /tmp/
MountLocation
$ attic init /tmp/ MountLocation /repository.attic
$ fusermount -u /tmp/ MountLocation
```

Encrypt a remote repository, using the following command: