

```
$ attic init --encryption=passphrase user@
remotehostname:backuprepository.attic
```

Create a backup in the root filesystem named 'YYYY-MM-DD-MySystem', using the command shown below:

```
NAME="`date +%Y-%m-%d` - MySystem "
$ attic create /MyDirectory/MyRepository.attic:$NAME / --do-
not-cross-mountpoints
```

Extract an entire archive, as follows:

```
$ attic extract /MyDirectory/MyRepository::MyDataFiles
```

Extract an entire archive and list files while processing, using the command given below:

```
$ attic extract -v /MyDirectory/MyRepository::my-files
```

Extract the 'src' directory using the following command:

```
$ attic extract /MyDirectory/MyRepository::my-files home/
USERNAME/src
```

To extract the 'src' directory but exclude object files, use the following command:

```
$ attic extract /MyDirectory/MyRepository::my-files home/
USERNAME/src --exclude '*.o'
```

Repository pruning: The repository is pruned to remove archives that do not match any of the mentioned preservation or storage options. Pruning is used to keep specific historic backups. For example, '-d 2' refers to keeping the last two days' backup. 

By: Dr Gaurav Kumar

The author is the MD of Magma Research and Consultancy Pvt Ltd, Ambala Cantt. He is associated with a number of academic institutes, where he delivers lectures and conducts technical workshops on the latest technologies and tools. E-mail: kumargaurav.in@gmail.com

Continued from page no...55

it, the topology just starts the POX controller so it should be connected to the controller. The default remote controller runs on the IP address 127.0.0.1 with the 6633 port. Dpctl is a management utility that enables some control over the OpenFlow switch. It shows the current state of the data path, including its features, configuration, and flow tables entries.

In Figures 2 and 3 h1, h2 and h3 are the network nodes which are connected with S1 OpenvSwitch (a virtual switch).

The simulation of a Mininet custom network topology is shown in the following example:

```
from mininet.topo import Topo
class MyTopo( Topo ):
    "Simple topology example."
    def __init__( self ):
        "Create custom topo."
        # Initialize topology
        Topo.__init__( self )
        # Add hosts and switches
        leftHost = self.addHost( 'h1' )
        rightHost = self.addHost( 'h2' )
        leftSwitch = self.addSwitch( 's3' )
        rightSwitch = self.addSwitch( 's4' )
        # Add links
        self.addLink( leftHost, leftSwitch )
        self.addLink( leftSwitch, rightSwitch )
        self.addLink( rightSwitch, rightHost )
        tops = { 'mytopo': ( lambda: MyTopo() ) }
```

Important classes, methods, functions and variables in the preceding code include:

Topo: The base class for Mininet *topologies*

addSwitch(): This adds a switch to a topology and returns the switch name

addHost(): This adds a host to a topology and returns the host name

addLink(): Adds a bi-directional link to a topology (and returns a link key, but this is not important). Links in Mininet are bi-directional unless mentioned otherwise.

Mininet: This is the main class to create and manage a network. 

References

- [1] <http://mininet.org/sample-workflow/>
- [2] <http://ofworkshop.blogspot.in/2013/10/build-your-network-topology-in-mininet.html>
- [3] <http://mininet.org/download>
- [4] <http://mininet.org/walkthrough/#part-1-everyday-mininet-usage>
- [5] <https://github.com/mininet/mininet/blob/master/custom/topo-2sw-2host.py>

By: Jitendra Bhatia and Prakash Patel

Jitendra Bhatia works as an assistant professor at Nirma University. You can contact him at jitendra.bhatia@nirmauni.ac.in, or <http://www.nirmauni.ac.in/ITNU/Faculty/Prof-Jitendra-Bhagwandas-Bhatia>

Prakash Patel works as an assistant professor at Nirma University. You can contact him at prakash.patel@nirmauni.ac.in