

Figure 1: Single host configuration




Figure 2: Dual host configuration

Install Rsyslog on both the hosts, Ubuntu1404ts1 and Ubuntu1404ts2, as follows:

```
sudo apt-get install rsyslog
```

Install *rsyslog-mysql* for MySQL support on Ubuntu1404ts2, using the following command:

```
sudo apt-get install rsyslog-mysql
```



Note: 1. Select 'No' if the installer asks to configure the database with *dbconfig-common* at this stage, and we will do it manually.
2. As part of dependencies for *rsyslog-mysql*, *mysql-client* also gets installed here.

Install *mysql-server* on Ubuntu1404ts2 by issuing the following command:

```
sudo apt-get install mysql-server
```

Now, let's create the required database structure in a MySQL server to store log messages, for which we need the database schema definition given in the *createDB.sql* file available in the Rsyslog source archive. I have taken the file from the Rsyslog version 7.4.10 source archive at <http://www.rsyslog.com/files/download/rsyslog/rsyslog-7.4.10.tar.gz>. The path to the file is */rsyslog-7.4.10/plugins/ommysql/createDB.sql*.

To create the database structure, run the following command in the Ubuntu1404ts2 host:




Figure 3: Dual host with remote DB configuration




Figure 4: Triple host with a Rsyslog relay server




Figure 5: Basic work-flow

```
mysql -u root -p < createDB.sql
```

Or if you can't get the above SQL file, you can copy-paste the following SQL commands at the MySQL console to create the required database structure:

```
CREATE DATABASE Syslog;
USE Syslog;
CREATE TABLE SystemEvents
(
    ID int unsigned not null auto_increment primary key,
    CustomerID bigint,
    ReceivedAt datetime NULL,
    DeviceReportedTime datetime NULL,
    Facility smallint NULL,
    Priority smallint NULL,
    FromHost varchar(60) NULL,
    Message text,
    NTSeverity int NULL,
    Importance int NULL,
    EventSource varchar(60),
    EventUser varchar(60) NULL,
    EventCategory int NULL,
    EventID int NULL,
    EventBinaryData text NULL,
```