

window (*Man ls*) using *C-M-v* (Ctrl-Alt-v), and scroll back using *C-M-shift-v* (Ctrl-Alt-Shift-v).

You can list all the available, active key-bindings using the *C-h b* command.

The *C-h f* shortcut is used to provide documentation for a function available in your installed version of GNU Emacs. For example, if you use *C-h f*, it will prompt you with the message 'Describe function:'. If you input 'scroll-other-window', it will open a new buffer and window titled 'Help' with the description and usage of the function. The output as seen in GNU Emacs 24.3.1 is shown below:

```
scroll-other-window is an interactive built-in function in
`C source
code'.
```

```
It is bound to <M-next>, C-M-v, ESC <next>.
```

```
(scroll-other-window &optional ARG)
```

```
Scroll next window upward ARG lines; or near full screen if
no ARG.
```

```
A near full screen is `next-screen-context-lines' less than
a full screen.
```

```
The next window is the one below the current one; or the one
at the top
```

```
if the current one is at the bottom. Negative ARG means
scroll downward.
```

```
If ARG is the atom `-', scroll downward by nearly full
screen.
```

```
When calling from a program, supply as argument a number,
nil, or `-'.
```

```
If `other-window-scroll-buffer' is non-nil, scroll the window
showing that buffer, popping the buffer up if necessary.
```

```
If in the minibuffer, `minibuffer-scroll-window' if non-nil
specifies the window to scroll. This takes precedence over
`other-window-scroll-buffer'.
```

```
[back]
```

On the other hand, if you know the command, and would like to get help related to it, you can use the *C-h k* command. This will prompt you with the message, 'Describe key (or click or menu item):'. You must key in the actual shortcut, for example, *C-h b*, and it will update the buffer 'Help', and open it in a new window, showing the description for the shortcut as seen below:

```
C-h b runs the command describe-bindings, which is an
interactive
compiled Lisp function.
```

```
It is bound to C-h b, <f1> b, <help> b, <menu-bar> <help-
menu>
<describe> <list-keybindings>.
```

```
(describe-bindings &optional PREFIX BUFFER)
```

```
Show a list of all defined keys, and their definitions.
We put that list in a buffer, and display the buffer.
```

```
The optional argument PREFIX, if non-nil, should be a key
sequence;
then we display only bindings that start with that prefix.
The optional argument BUFFER specifies which buffer's bindings
to display (default, the current buffer). BUFFER can be a
buffer
or a buffer name.
```

```
[back]
```

You are encouraged to try out all the commands so that you understand what actions they perform. When you use GNU Emacs as your main text editor, you will be able to regularly practice these commands, and master them. 

By: Shakthi Kannan

The author is a Free Software enthusiast and blogs at shakthimaan.com.

Read more stories on LED at
www.electronicb2b.com

**TOP
LED STORIES**

- The latest in LED indoor displays
- The latest in LED street lights
- The latest in LED office lights
- Learn how to become a channel partner
- Read about brand strategies

**ELECTRONICS
B2B
INDUSTRY IS AT A**

CLICK OF A BUTTON

Log on to www.electronicb2b.com and be in touch with the Electronics B2B Fraternity 24x7