

Example:

```
mp3player -dumpstream http://www.archive.org/download/  
CopyingIsNotTheft-Best/CINT_Nik_H264_720.ogv -dumpfile copy.ogg
```

—Jaganadh G, jaganadhg@gmail.com



Finding open sockets

Here is a sequence of commands to find out if anybody is doing anything to your system:

```
$ lsof
```

or as root

```
$ watch lsof -i
```

To list all open Internet files, use the following command:

```
$ lsof -i -U
```

You can also get very specific about ports. Use the following command as the 'root' for low ports.

```
$ lsof -i TCP:3306
```

Or, look at UDP ports as follows:

```
$ lsof -i UDP:1812
```

—Bhajan Lal, bhajan.lal@fiserv.com



Knowing your system's configuration

Most of you would like to have information about the system you are using. Here is one command that will display the information about the system's configuration.

```
$ uname -a
```

This command prints the following information: kernel name, network node hostname, kernel release, kernel version, machine hardware name, processor type, and operating system.

—Amol Takkalki, takkalki.amol@gmail.com



Change the 'Prompt' style

Are you getting bored with your Bash shell's \$# sign? Use the following commands to change it:

```
$ PS1='Yours' to change the Prompt characters.
```

```
$PS1="Yours" to change secondary prompt (By default it is >)
```

```
$PS2="Yours" Note: Replace 'yours' with your choice of word with quoted strings.
```

—Vikas Malbiya, vm94@in.com



Examples of most common aliases

An alias can help make your life easy. Listed below are a few examples that can be used to make your daily tasks, easier.

Open the last modified file in Vim

```
alias Vim='vim `ls -t | head -1`'
```

Grep for a bash process

```
alias psg='ps -aux | grep bash'
```

The following command lists hidden files with an indicator and colour:

```
alias ls='ls -aF --color=always'
```

To make basic commands interactive and verbose, type the following command:

```
alias cp='cp -iv'      # interactive, verbose  
alias rm='rm -i'       # interactive  
alias mv='mv -iv'      # interactive, verbose  
alias grep='grep -i'   # ignore case
```

For file system disk space usage, use the following command:

```
alias dus='df -h'
```

Now, if you want to temporarily stop using aliases, type the command given below:

```
$ \aliasname
```

To remove an alias, type the following command:

```
$ unalias aliasname
```

To remove all aliases, use the following command:

```
$ unalias -a
```

—Vijay Soni, vs4vijay@gmail.com



Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in LFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get an LFY T-shirt.