

`doc/sync/primary-backup.sh` to `/etc/contrackd`. Edit the `/etc/contrackd/contrackd.conf` file and change the following parameters:

- 1] `IPv4_interface 172.16.1.252` (Add your sync interface IP; in our case, it is 172.16.1.252)
- 2] `Interface eth1` (Specify the interface that will act as the sync interface)
- 3] `State Accept {`
`ESTABLISHED CLOSED TIME_WAIT`
`CLOSE_WAIT for TCP`
`}`

Now edit `/etc/keepalived/keepalived.conf`. Given below is a sample file that has been modified according to our needs, with 2 VRRP groups with VRRP IPs:

```
vrrp_sync_group G1 { # must be before vrrp_instance declaration
group {
    VI_1
    VI_2
}
notify_master "/etc/contrackd/primary-backup.sh primary"
notify_backup "/etc/contrackd/primary-backup.sh backup"
notify_fault "/etc/contrackd/primary-backup.sh fault"
}

vrrp_instance VI_1 {
    interface eth0
    state MASTER
    virtual_router_id 61
    priority 90
    advert_int 2
    authentication {
        auth_type PASS
        auth_pass myfirewall
    }
    virtual_ipaddress {
        192.168.178.254 # default CIDR mask is /32
    }
}

vrrp_instance VI_2 {
    interface eth2
    state MASTER
    virtual_router_id 62
    priority 90
    advert_int 2
    authentication {
        auth_type PASS
        auth_pass myfirewall
    }
    virtual_ipaddress {
        10.1.1.254
    }
}
```



Note: Make sure both the files on each cluster node are identical, except for priority. On a secondary node, you can keep the priority higher than on the primary node. You can always edit this file according to your needs.

Please refer to the following `keepalived.conf` file from Firewall2, and compare 'priority':

```
vrrp_sync_group G1 { # must be before vrrp_instance declaration
group {
    VI_1
    VI_2
}

notify_master "/etc/contrackd/primary-backup.sh primary"
notify_backup "/etc/contrackd/primary-backup.sh backup"
notify_fault "/etc/contrackd/primary-backup.sh fault"
}

vrrp_instance VI_1 {
    interface eth0
    state MASTER
    virtual_router_id 61
    priority 90
    advert_int 2
    authentication {
        auth_type PASS
        auth_pass myfirewall
    }
    virtual_ipaddress {
        192.168.178.254 # default CIDR mask is /32
    }
}

vrrp_instance VI_2 {
    interface eth2
    state MASTER
    virtual_router_id 62
    priority 90
    advert_int 2
    authentication {
        auth_type PASS
        auth_pass myfirewall
    }
    virtual_ipaddress {
        10.1.1.254
    }
}
```

Now start the `keepalived` and `contrackd` daemons and keep an eye on the system's `syslog` messages. You will soon find VRRP messages, where `keepalived` will advertise that it