



Figure 9: All user page

```
private static final int DATABASE_VERSION = 1;
public static final String SAKET_TABLE_NAME = "login";
private static final String SAKET_TABLE_CREATE =
    "CREATE TABLE " + SAKET_TABLE_NAME + "(" +
    " _id INTEGER PRIMARY KEY AUTOINCREMENT, " +
    " username TEXT NOT NULL, password TEXT NOT
    NULL, email
    TEXT NOT NULL);";
private static final String SAKET_DB_ADMIN = "INSERT INTO
    "+SAKET_TABLE_NAME+"values(1, admin, password, admin@gmail.
    com);";

public DBHelper(Context context) {
    super(context, DATABASE_NAME, null, DATABASE_VERSION);
    System.out.println("In constructor");
}

/* (non-Javadoc)
 * @see android.database.sqlite.SQLiteOpenHelper#onCreate(android.
    database.sqlite.SQLiteDatabase)
 */
@Override
public void onCreate(SQLiteDatabase db) {
    try{
        //Create Database
        db.execSQL(SAKET_TABLE_CREATE);

        //create admin account
        db.execSQL(SAKET_DB_ADMIN);
        System.out.println("In onCreate");
    } catch (Exception e) {
        e.printStackTrace();
    }
}

/* (non-Javadoc)
 * @see android.database.sqlite.SQLiteOpenHelper#onUpgrade(android.
    database.sqlite.SQLiteDatabase, int, int)
 */
@Override
```



Figure 10: Admin failed

```
public void onUpgrade(SQLiteDatabase arg0, int oldVersion,
    int newVersion) {
}
}
```

In this class, we create the database in the *onCreate()* method. This method is invoked when the application is installed on the device. The *onUpgrade()* method is invoked when there is an existing database, and if there are some changes that need to be done to it.

In Android, to use *SQLiteDatabase*, we need to extend the *SQLiteOpenHelper* class. It is mandatory to have a constructor, and it is also mandatory to have *DATABASE NAME* and a *DATABASE VERSION* that need to be passed to the *SQLiteOpenHelper* class constructor.

In the *onCreate()* method, we execute the *CREATE* statement, using the API method *db.execSQL(String query)*. In this method, we also create a default *admin* account, with the default password set to "*admin*".

The *AdminPage* activity is the admin page that the application presents. In this activity, we just verify the admin password in the class itself, because we already know the password—but it is for you as a developer to decide whether you want to verify the password of the admin account via a database query as well. It is inherently insecure to have an unchangeable default admin password, so on security principles, for a real-life application, you should certainly provide the ability to change the admin password. However, this being only a demo application, we have not added in the extra code.

```
mPassword = (EditText)findViewById(R.id.editPassword);

String pass = mPassword.getText().toString();
if (pass.equals("") || pass == null){
    Toast.makeText(getApplicationContext(), "Password Missing",
        Toast.LENGTH_SHORT).show();
}
```