

```

    }else{
        if(pass.equals("admin")){
            Toast.makeText(getApplicationContext(), "Retrieving
Data", Toast.LENGTH_SHORT).show();
            retrieveEntries();
        }else{
            Toast.makeText(getApplicationContext(), "Admin Login
Failed", Toast.LENGTH_SHORT).show();
        }
    }
}

```

When the admin logs in, then he or she is shown a list of all the registered users—or we *Toast* the admin with a suitable error message, as shown in Figures 9 and 10.

```

public void retrieveEntries(){
    try{
        SQLiteDatabase db = myDb.getReadableDatabase();
        String[] columns = {"username","email"};
        Cursor cursor = db.query(DbHelper.SAKET_TABLE_NAME,
columns, null, null, null, null, null);
        if(cursor != null){
            System.out.println("database showing");
            startManagingCursor(cursor);
            showDatabase(cursor);
        }
        System.out.println("Cursor NULL");
    } catch(Exception e) {
        e.printStackTrace();
    }
}

public void showDatabase(Cursor cursor) {
    StringBuilder ret = new StringBuilder("Database Values\n\n");
    ret.append("\nUsername\t Email ID\n\n");
    while (cursor.moveToNext()) {
        String uname = cursor.getString(0);
        String email = cursor.getString(1);
        ret.append(uname+"\t\t\t"+email+"\n\n");
    }
    TextView result = new TextView(this);
    result.setText(ret);
    setContentView(result);
}

public void onDestroy(){
    super.onDestroy();
    myDb.close();
    finish();
}

/* (non-Javadoc)
 * @see android.app.Activity#onBackPressed()

```

```

*/
@Override
public void onBackPressed() {
    super.onBackPressed();

    Intent i = new Intent(AdminPage.this, DatabaseActivity.
class);
    startActivity(i);
    finish();
}
}

```

In the admin page, the above-mentioned two methods are used to retrieve the entries from the database, and show them to the admin in a *TextView*. In the above code:

- The *retrieveEntries()* method queries the database for all the users created.
- The *showDatabase()* method displays all the data obtained in the *CURSOR* in a *TextView*. The data from the cursor is retrieved by processing the cursor in a *while* loop, querying the columns based on their index. A *StringBuilder* object is used to build the final string containing all the data from the cursor, which is then fed to the *TextView* for display.
- The *onBackPressed()* method is used to alter the action of the back key on the device to suit our application. Developers can then fire intents to decide the action they want to perform.

There are a lot of changes that can be applied to the code regarding the authentication mechanism; there is a provision to add many other exceptions, and prompt the user with a suitable message. Readers are free to contribute to this piece of code for their own understanding. You can pull a clone of this project from my Github repository (http://bit.ly/saket_github_loginpage) and play around with the code. There is another improvement that can be made to the code, by introducing transaction APIs like *beginTransaction()*, *setTransactionSuccessful()*, etc. You can play around with these APIs, and enhance their applications' database transactions to be more secure and atomic. These APIs also help application transactions to be compliant with the ACID definition of a database transaction: A – Atomicity; C – Concurrency; I – Integrity; and D – Durability.

This is all I have for you in this article. We'll explore another interesting concept of Android Application Development in the next issue. Till then, happy coding! 

By: Saketkumar Srivastav

The author is an open source enthusiast, and an Android developer. Find him online at http://bit.ly/saket_blog and http://bit.ly/saket_wordpress.