

```
rotate 12
# create new (empty) log files after rotating old ones
create
# uncomment this if you want your log files compressed
compress
# RPM packages drop log rotation information into this directory
include /etc/logrotate.d
# no packages own wtmp -- we'll rotate them here

/var/log/wtmp
{
    monthly
    create 0664 root utmp
    rotate 1
}

# system-specific logs may be also be configured here.
```

This will enable you to keep your logs for 12 months in a compressed format.

—Chandan V, cdn.kit@gmail.com

List the shared library dependencies

Want to know what the libraries shared by your program are? Here's a tool called, "ldd"

For example, let us create a file hello.c as shown below using any text editor:

```
$ cat hello.c

#include <stdio.h>

int main()
{
    printf("Hello, World...\n");

    return 0;
}
```

Create the executable:

```
$ gcc hello.c -o hello
```

List the dependencies:

```
$ ldd hello

linux-gate.so.1 => (0x007d0000)

libc.so.6 => /lib/tls/i686/cmov/libc.so.6 (0x00100000)
```

```
/lib/ld-linux.so.2 (0x003e7000)
```

—Chandan V, cdn.kit@gmail.com



Find dead symbolic links

Would you like to get rid of dead symbolic links? Run the following command:

```
find . -type l | perl -line 'print if ! -e'
```

—Remin Raphael, remin@smartgeek.in



Displaying a particular line of a text file

The head command gives the top 10 lines of a text file.

```
head filename
```

You can give a line number as a parameter. To view the top 5 lines, the command is:

```
head -5 filename
```

The tail command gives the last 10 lines of a text file.

```
tail filename
```

As in the previous command, you can give the number of lines you want to be displayed as a parameter.

```
tail -5 filename
```

You can display any single line of a file by using a combination of the head and tail. To display the 10th line, give the following command:

```
head -10 filename | tail -1
```

You can use the head and tail command to view a portion of a text file. For example, to see the 30th to the 35th line of a file, give the following command:

```
head -35 filename | tail -6
```

—S. Sathyanarayanan, sathyanarayanan_s@yahoo.com

END →

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in LFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get an LFY T-shirt.