

- *who am i*
- *who is this*

These commands give information about all the users logged in to a UNIX terminal.

Do you want to know what other users or your friends in the UNIX lab are doing? Then the command you need to use is 'w'.

- *w* — gives information about users and also tells what they are doing. It gives the port number, login time and also the last command that they executed.
- *who* — The *who* command gives the login time, date and also the port number.
- *whoami* — The *whoami* gives information about the user id. It is similar to *id -un* and just gives a one-word output on the standard output.
- *who am i* — The *whoami* and the *who am i* are completely different commands. The *who am i* command gives information about the port number of the user and the login time.
- *who is this* — The *who am i* and the *who is this* commands give the same output.

Here's a small shell script (let's name it *Status.sh*) to check if a user is logged in or not, and what he or she is doing:

```
#! /bin/sh
# Status.sh
if
    w | grep "$1" > /dev/null
then
    echo $1 Logged in
    echo Current Status is :
    w | grep "$1"
else
    echo $1 is not Logged in
fi
```

Now run the following command:

```
$ sh Status.sh <username>
```

If the user 'username' is logged in, then it will give all the required details, otherwise it will return:

```
<username> is not Logged in
```

Enjoy your UNIX lab!

—Sistla Venkata Abhishek, svabhishek@gmail.com



## Create and capture SSH logs

If you want to capture all the activities of the SSH server on your client machine, run this command:

```
ssh username@hostname | tee -a logfile.log
```

...where *logfile.log* is created on your client machine in the current directory.

—Bhajan Lal, bhajan.verma@gmail.com



## Viewing log files generated by servers

Today Linux is used for deployment of application servers like Glassfish, WebLogic, WebSphere, JBoss, Tomcat, etc, for J2EE applications.

These servers generate log files or redirect the console logs to a text file (like *SystemOut.log* for WebSphere).

When we use GUI clients we can use editors to view those large-sized files. But when accessing the server using Remote shell, it is quite difficult to view these files. Here is a handy tool, 'less', which comes to your rescue:

```
less ~/logs/server1/SystemOut.log
```

This displays the content of the file just like *cat*.

Once the content is displayed, if you press 'F' (without quotes) you can see a *live* display on the screen of whatever the application server writes.

To stop the *live* view, press *Ctrl+c*

After that, press:

- *d* to scroll forward
- *b* to scroll backward
- *q* to exit less
- *F* to go back to live view.

You can check out the manual for more options.

—Pranavam S, pranavam.s@gmail.com



## Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in LFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at [www.linuxforu.com](http://www.linuxforu.com). The sender of each published tip will get an LFY T-shirt.