

in comparison with the Vala code required to achieve the same output.

```
[indent=4]
init
    print "Hello to FOSS from Genie!!!"
```

Compile two Genie source files (the code is shown below) with the command `valac -o testoop testoop1.gs testoop2.gs` and run the executable `testoop` to try OOP concepts in Genie.

testoop1.gs:

```
[indent = 4]

class GOp1 : GOp
    prop _iv : int
    prop _dv : double

    init
        this._iv = 8
        this._dv = 7.898

    construct(ival : int, dval : double)
        iv = ival
        dv = dval

    def getState1()
        print "\n iv : %d, dv : %f\n", iv, dv

    def setState1(ival : int, dval : double)
        setState(ival, dval)
```

testoop2.gs:

```
[indent = 4]

class GOp : Object
    prop _iv : int
    prop _dv : double

    init
        _iv = 7
        _dv = 3.14

    def getState()
        print "\n _iv : %d, _dv : %f\n", _iv, _dv

    def setState(ival : int, dval : double)
        _iv = ival
        _dv = dval

init
```

```
var goop = new GOp()

goop.getState()
goop.setState(89, 56.789)
goop.getState()

var goop1 = new GOp1(56, 89.45657)
goop1.getState1()
```

This Genie code also demonstrates concepts introduced in the Vala section, like singular super-class inheritance, properties, code in multiple files, etc.

Now let's play with some GTK+ applications in Genie. Compile `testgtk.gs` with `valac --pkg gtk+-2.0 testgtk.gs` and run it.

testgtk.gs:

```
[indent = 4]

uses Gtk

init

Gtk.init(ref args)
var test = new TestWindow()
test.show_all()
Gtk.main();

class TestWindow : Window
    init
        title = "GTK+ sample in Genie"
        default_height = 250
        default_width = 250
        window_position = WindowPosition.CENTER
        destroy += Gtk.main_quit
        var button = new Button.with_label("Bang me!!")
        button.clicked += def(btn)
            title = "Hello to GTK+ from Genie."
            btn.label = "Hello to GTK+ from Genie."
        add(button)
```

The output of the GTK+ Genie sample is shown in Figure 4.

The next GTK+ example, `fontselectiondialog.gs`, is taken from the Genie examples site mentioned in the *References* section. It explores invoking a GTK+ font-selection dialogue box from Genie. To compile it, run `valac -o fontselectiondialog --pkg gtk+-2.0 --pkg pango fontselectiondialog.gs`.

The running `fontselectiondialog` is shown in Figure 4.

Want to have an edge over others?

Master LINUX



Read
LINUX For You

For more info, log on to:

www.linuxforu.com



ASIA'S FIRST
LINUX
MAGAZINE

LINUX
THE COMPLETE MAGAZINE ON LINUX SYSTEMS
ForYou