

Create a new WebTest project

WebTest contains a utility script to create a new project, with some examples ready to run. Open a new shell and execute the following command. You will be prompted for the name of the new project; in the example below, we name it *newBuddy*. If you just hit *Enter*, the default name *myWebTestProject* will be used.

```
$ webtest.sh -f webtest.xml wt.createProject
Buildfile: webtest.xml
Will use java
Buildfile: webtest.xml
wt.init:
wt.createProject:
    [input] Enter your WebTest project name: [myWebTestProject] newBuddy
    [mkdir] Created dir: /home/bhuvan/projects/cubit/tests/functional/
    webtest/newBuddy
    [copy] Copying 12 files to /home/bhuvan/projects/cubit/tests/functional/
    webtest/newBuddy
    [echo]
    [echo] Your WebTest project >newBuddy< has been successfully created
    with some demo
    [echo] tests to get started.
    [echo] You can now just go to >/home/bhuvan/projects/cubit/tests/
    functional/webtest/newBuddy< and run ant.
    [echo]
BUILD SUCCESSFUL
Total time: 7 seconds
```

Run the demo tests

Your newly-created project contains some ready-to-run Web tests that you can use as templates. You can run them by moving to the project directory and executing the following command. If you are behind a proxy, edit the *build.xml* Ant file to configure the proxy connection.

```
$ webtest.sh
```

You should see some activity in the shell window, and after a few seconds you will see the following output:

```
wt.openResultFile:
    [echo] Opening result file /home/bhuvan/projects/cubit/tests/functional/
    webtest/newBuddy/results/index.html with firefox
wt.junitLikeReports:
    [xslt] Processing /home/bhuvan/projects/cubit/tests/functional/webtest/
    newBuddy/results/WebTestOverview.xml to
    /home/bhuvan/projects/cubit/tests/functional/webtest/newBuddy/results/
    WebTestOverview.junit.xml
    [xslt] Loading stylesheet /home/bhuvan/projects/cubit/tests/functional/
    webtest/resources/WebTestOverview2JUnit.xsl
wt.countWebTestResults:
wt.full:
BUILD FAILED
/home/bhuvan/projects/cubit/tests/functional/webtest/webtest.xml:427: 4 of 6
webtests have failed (2 successful)!
```



Figure 1: Sample WebTest report

Total time: 48 seconds

An HTML report file like the one shown in Figure 1 should be displayed in your favourite browser.

Note: The demo test suite deployed while you created the project includes six tests, out of which four are expected to fail, as reflected in the sample report above.

Sample WebTest Script

A sample WebTest script is displayed below. It is shipped as part of the demo test suite when we create a WebTest project, as elaborated in the previous section. For details, refer to *newBuddy/tests/googleWebTest.xml*.

```
<?xml version="1.0"?>
<!DOCTYPE project SYSTEM "../dtd/Project.dtd">
<project default="test">
  <target name="test">
    <webtest name="check that WebTest is Google's top 'WebTest' result">
      <invoke url="http://www.google.com/ncr" description="Go to Google (in
      English)"/>
      <verifyTitle text="Google" />
      <setInputField name="q" value="WebTest" />
      <clickButton label="I'm Feeling Lucky" />
      <verifyTitle text="Canoo WebTest" />
    </webtest>
  </target>
</project>
```

As the script's name implies, the above test is specific to Google. It accesses the Google search engine, verifies it has received the Google home page, types the word *WebTest* in the input field, and clicks the *I'm Feeling Lucky* button. The title in the response page should be *Canoo WebTest*. Though the XML tags used in the above test are somewhat self-explanatory, let's explore each of them for the sake of clarity:

- **project** – Denotes a WebTest project
- **target** – Denotes a unique Ant target in WebTest. A test suite may have multiple targets
- **webtest** – Provides the ability to specify and execute functional tests for a Web-based application
- **invoke** – Executes a request to a particular URL
- **verifyTitle** – Verifies the text in the HTML title tag for the returned page against the specified text