

- **CTRL+R** : This is used to search for a command in command history. For example, yesterday or a few hours back you typed 'a very, very long command' and you need the same command again. Then hit CTRL+R and type the first few letters of the command.
- **CTRL+T** : Transposes characters. For example, let's assume that you wanted to type the *date* command and ended up typing the following:

```
$ date
```

Sure, you can delete the last two characters and retype it again, but wait! You can also hit CTRL+t and you are done.

— Mohana Sundaram N, mohan.linux@yahoo.com



Access a Windows share from Bash

Ever wanted to access a Windows share from your terminal? Well, using mount and cifs/samba, this is possible. Make sure you have *smbfs/cifs* support. We need to make a directory on our hard disk where we can mount the Windows share.

```
mkdir /mnt/location
```

We are now ready to mount the filesystem on our newly created directory */mnt/location/*.

To mount using cifs, use the following code:

```
mount -t cifs //server-ip-or-name/share /mnt/location -o
username=user,password=pass,domain=DOMAIN
```

When we're done working on the share, we should exit the directory or close any programs that are accessing it, and then *umount* the Windows share by using the following commands:

```
cd /
umount /mnt/location
```

— Anand Nayyar, anand_nayyar@yahoo.co.in



Data recovery in Ubuntu

Install *ddrescue* tools:

```
sudo apt-get install ddrescue
```

Connect the failed disk to your system:

```
sudo dd_rescue /dev/sdb disk-image.img
Summary for /dev/sdb -> disk-image.img:: 0.0k, success: 228352.0k
dd_rescue: (info): ipos: 229376.0k, opos: 229376.0k, xferd: 229376.0k
errs: 0, errxf: 0.0k, success: 229376.0k
```

```
+curr.rate: 26249kB/s, avg.rate: 28391kB/s, avg.load: 13.5%
```

We can now mount this image on our system and take a look at the files:

```
mount -t ext3 -o loop disk-image.img /mnt/tmp
```

— Anand Nayyar, anand_nayyar@yahoo.co.in



Check and monitor CPU core temperatures

Feel like checking your CPU temperature ratings? Well, it is very easy on Ubuntu. First we need to get some packages:

```
sudo apt-get install lm-sensors sensors
```

Next step is to probe for modules and drivers—run the following command and answer "YES" to the questions:

```
sudo sensors-detect
```

The above step will generate some code at the end. Add the same to your */etc/modules* file. You will be given an option to add the text automatically otherwise you can edit the file manually. Now reboot your system and simply type the following command to check the core temperature:

```
sensors
```

— Aditya Krishna Haas Rayaprolu, krishnaaas@gmail.com

Live interrupts details

To watch the live interrupt changes in your system run:

```
watch -d 'cat /proc/interrupts'
```

— Vineesh kumar, vineeshhere@gmail.com



Make the commands you type invisible

To hide the user input characters (for instance: password information) to be displayed on screen, use the terminal line setting command, *stty -echo*. Whatever the user enters after this command will NOT be displayed in the screen. To then make the input characters get displayed to the screen, use *stty echo*.

— Rajesh Sankaran, rajesh.raji@wipro.com

END - -

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in LFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get an LFY T-shirt.