

Most of us are familiar with the KILL command, but here is another feature of the KILL command, which can also prove helpful:

```
#kill -STOP 10067 (where 10067 is process id)
```

```
#kill -CONT 10067 (where 10067 is process id)
```

This will stop the given process since it has been not restarted with the command-CONT

—Santhosh Kothuru, kothurusantosh@gmail.com

Changing the default port for the SSH user

The default port for the SSH user is 22. But we can change the default port to some other port, if, for instance, you want to run the ssh service on port 99 instead of 22.

Make the following changes:

Open files in any text editor

```
#emacs /etc/ssh/ssh_config
```

```
#emacs /etc/ssh/sshd_config
```

Search for the port setting. By default, the port setting is 22.

Change port 22 to port 99, save and exit your text editor.

```
#port = 99
```

You can change and run the ssh service on any port. But make sure other services are not running on that port.

—Santhosh Kothuru, kothurusantosh@gmail.com

Stop your computer from answering to ping

Here is a simple step designed to prevent your computer from responding to ping.

```
echo 1 > /proc/sys/net/ipv4/icmp_echo_ignore_all
```

After running this, you will not receive a reply if pinged from other computers. To reset the settings and turn the default settings on, simply type the following command:

```
echo 0 > /proc/sys/net/ipv4/icmp_echo_ignore_all
```

—Santhosh Kothuru, kothurusantosh@gmail.com

For a quick reboot

Rebooting Linux takes quite a long time. For a quick reboot, we need to fire the following command:

```
# reboot -f
```

But be careful with this command because it doesn't save any recent configuration changes related to grub and partitions.

—Adarsh, addi_adarsh@yahoo.co.in

A command to display all live hosts in the network

Network administrators may need a command that will display all the live hosts in their subnet or network. Here is a command for the purpose:

```
for i in {1..10}; do ping -c1 192.168.0.$i; done | grep "ttl"
```

This will print all reply summaries from live hosts.

In this command, I used shell programming to ping all hosts in my subnet 192.168.0.0/24.

We can also use another application called *fping*

Install *fping* by executing the following command:

```
sudo apt-get install fping
```

To query the network for live hosts in the subnet 192.168.1.0/24 give the following command:

```
fping -g 192.168.1.0/24 | grep "alive"
```

...or use:

```
fping -g 192.168.1.0 192.168.1.255 | grep "alive"
```

—Kumar Vikramjeet, vik01@itimes.com

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in LFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get an LFY T-shirt.