

## Know the libraries used by a program



Here is a tip that will help you know what shared libraries are being used by a program.

For example, to figure out exactly which libraries are used by *ls*, run the following command:

```
ldd /bin/ls
```

The output will be a list of all shared libraries:

```
linux-gate.so.1 => (0xffff0000)
libselinux.so.1 => /lib/libselinux.so.1 (0xb786c000)
librt.so.1 => /lib/librt.so.1 (0xb7862000)
libcap.so.2 => /lib/libcap.so.2 (0xb785c000)
libacl.so.1 => /lib/libacl.so.1 (0xb7852000)
libc.so.6 => /lib/libc.so.6 (0xb76e4000)
libdl.so.2 => /lib/libdl.so.2 (0xb76df000)
/lib/ld-linux.so.2 (0xb78a4000)
libpthread.so.0 => /lib/libpthread.so.0 (0xb76c4000)
libattr.so.1 => /lib/libattr.so.1 (0xb76be000)
```

—Aarsh S Talati,  
aarshstatalati1989@gmail.com

## Print a file with line numbers



If you want a file with line numbers (say for printing), you can use the 'nl' command in Linux:

```
$ nl file.c
```

This prints the file with line numbers to standard output or this can be even redirected to a file as shown below:

```
$ nl file.c > output.txt
```

Here, *output.txt* will have the codes of *file.c* with each line having a line number.

—Phaniram Vallury,  
ramvvs@gmail.com

## Cut specific logs



If you need to cut specific logs from the complete log of any application, here is a tip that will be of help.

Open the log file in a vi editor and set the editor to display the line number:

```
vi server.log
```

```
:set nu
```

The above process will provide you the line numbers in the logs. You can then search for the specific string and note down the line number (e.g., 550). Now, note down the

last line number by using *Shift+G* (e.g., 780)

```
sed -n 550,780p server.log > threaddump.log
```

So the *threaddump* only contains lines from 550 to 780.

—Venkatesh R,  
venka.2k@gmail.com

## Reset ifconfig counters



As you can see, *ifconfig* keeps a couple of counters (RX/TX packets, RX/TX bytes, errors, dropped, overruns, frames and carrier collisions).

You can quickly spot if there is a problem by just looking at the *ifconfig* counters:

```
#ifconfig eth0
```

```
eth0      Link encap:Ethernet  HWaddr XX:XX:XX:XX:XX:XX
inet addr:192.168.0.2  Bcast:192.168.0.255  Mask:255.255.255.0
UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
RX packets:4233700943  errors:2  dropped:0  overruns:3  frame:5
TX packets:1917219659  errors:1  dropped:0  overruns:0
carrier:348
collisions:5753  txqueuelen:3000
RX bytes:1467520926 (1.3 GiB)  TX bytes:2299420437 (2.1 GiB)
```

You can now find out what driver is being used by the network interface, which you want to reset by using *ethtool*.

```
#ethtool -i eth0
```

```
driver: e100
version: 3.4.14-k4-NAPI
firmware-version: N/A
bus-info: 0000:01:07.0
```

```
# modprobe -r e100; modprobe e100; ifup eth0
```

This will reset all counters.

—Vinod Rana,  
rana3807@gmail.com

END

## Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in LFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at [www.linuxforu.com](http://www.linuxforu.com). The sender of each published tip will get an LFY T-shirt.