



Figure 6: Viewing PHP output

root, run the following commands (put 2 or 3 in place of * in the second-last line, depending on the version of PHP you use—5.2 or 5.3):

```
service zend-server stop
#allow port 10083 for http context to access UI whost#
semaphore port -a -t http_port_t -p tcp 10083
#mark binary or shared library as not requiring executable
stack#
execstack -c /usr/local/zend/lib/libssl.so.0.9.8
execstack -c /usr/local/zend/lib/libcrypto.so.0.9.8
execstack -c /usr/local/zend/lib/apache2/libphp5.so
execstack -c /usr/local/zend/lib/debugger/php-5.*./ZendDebugger.
so
execstack -c /usr/local/zend/lib/php_extensions/curl.so
```

If you face a problem in running `execstack`, install `prelink` with `yum install prelink`. Now we have to change the context, according to the SELinux policy:

```
chcon -R system_u:object_r:httpd_tmp_t /usr/local/zend/tmp
chcon -R system_u:object_r:httpd_log_t /usr/local/zend/var/log
chcon -R system_u:object_r:tmp_t /usr/local/zend/tmp/pagecache /
usr/local/zend/tmp/datacache
chcon -t textrel_shlib_t /usr/local/zend/lib/apache2/libphp5.so /
usr/lib*/libcintsh.so.11.1 \ /usr/lib*/libocius.so /usr/lib*/
libnzn11.so
```

Start the Zend Server with `/usr/local/zend/bin/zendctl.sh start` or `service zend-server start`. Now that you have completed the configuration, reboot the system. The SELinux policy will be set as *Enforcing* after reboot. Once again visit the Zend Server administrative interface, log in with the password you set previously and if it works, you've done it all right.

Now launch Zend Studio and create a new project (*File > New > Local PHP Project*). Give the project a suitable name, and click *Next*. Choose a host from the drop-down menu (Figure 4). For RPM/DEB installations, choose `http://localhost` (because Apache's distribution is used), and the rest may choose `http://localhost:10088` (as Zend Server modifies the configuration to listen on port 10088). Click *Next* and then *Finish*. You will get your project folder on the left panel of Zend Studio, as can be seen in Figure 5.

Right-click the folder and choose *New > PHP File*. Type in a new filename (see Figure 5). Click *Next > Finish*. In the new file, type the following code:

```
<?php
phpinfo();
```

?>

Save your file, set the run configuration to *Run as Web Application*, and press *Ctrl+F11* to run the program. You will get the PHP set-up information of your system in the IDE's internal browser (Figure 6). Now you are ready to begin any PHP project. Happy coding!

Some post-installation configuration

Every time you restart your Zend Server, you will get the following message in the terminal:

```
httpd: could not reliably determine the server's fully qualified
domain name, using fe80::221:ff:fec9:de31 for servername
```

To solve this problem, add the following line to `/etc/httpd/conf` (the location may vary depending on the distribution). Put the name of your server host in the brackets; in my case, it is `localhost`:

```
ServerName [server name]
```

Restart Zend Server, and there you go! You have set up the Zend PHP IDE with Zend Server. **END** 

References

- [1] <http://www.zend.com/en/resources/zend-documentation>
- [2] http://docs.redhat.com/docs/en-US/Red_Hat_Enterprise_Linux/6/html/Managing_Confined_Services/index.html
- [3] <http://fedoraproject.org/>

By: Rahul Gupta

The author loves working around new technologies, especially those related to the Web and Linux. He'll be happy to receive queries or suggestions at rahulgupta172@yahoo.com.