



TIPS & TRICKS

Secure your file from other users

 Here is a small tip that will secure the files owned by you from other users.

```
$chmod +t <file-name>
```

Now, check the permission:

```
$ls -l
```

You will see a file permission like the one given below:

```
-rwxr-x--r--f-T
```

Now, no one other than the *root* user can delete your files.

—Sarju R Hansaliya,
same.mastermind@gmail.com

Redirect output from the console to the clipboard in Linux systems

 Linux systems do not have *pbcopy* or *pbpaste* commands like Mac OS X does—but installing *xclip* or *xsel* (via a package management system, or directly from source) achieves the same function. Once installed, add relevant aliases to the *~/.bashrc* file, as follows.

For *xclip*:

```
alias copy=xclip -selection clipboard
alias paste=xclip -selection clipboard
```

For *xsel*:

```
alias copy='xsel --clipboard --input'
alias paste='xsel --clipboard --output'
```

Once that's done, restart the terminal, and you are good to go! Just pipe the output of a command to the newly created alias *copy* to redirect the output to the clipboard (see below), and you can use the content in another command by using the alias *paste*. For example:

```
$pwd | copy
$paste -o
/home/rushyang/LinuxForYou
```

—Rushyang Darji,
rushyangdarji@gmail.com

Avoid typing long commands

 When working with the command-line, you may need to type long commands frequently. To save yourself from typing, create an *alias* for each command. For example, to monitor */var/log/messages*, as the *root*, instead of typing *tail -f /var/log/messages* every time, you can instead create an alias, as follows:

```
#alias msg='tail -f /var/log/messages'
```

You can then just run *msg* instead of the longer command. You can see the list of defined aliases by running *alias* without any parameters. To remove an alias, use something like the following:

```
#unalias msg
```

Unless you add the alias definition commands to your *~/.bashrc*, they are effective only till the end of the shell session.

—Chekkizhar,
chekkezharayy@gmail.com

Make a program default

 Debian and its derivatives have a hassle-free way of allowing you to make an application the default for all similar files. For example, to check what executable provides '*x-terminal-emulator*', you can run the following command:

```
update-alternatives --display x-terminal-emulator
```

If you want to change the default, then run the command given below:

```
update-alternatives --config x-terminal-emulator
```