

Find your MySQL configuration file

 We often have to administer a system that has been set up by someone else. In such a situation, it's difficult to find the correct configuration files for different applications. Here is a tip to find the correct configuration file for MySQL:

```
mysql -? | grep ".cnf"
```

—Remin Raphael,
remin@smartgeek.in

Use YUM to download a package

 Often, you need to download rpm packages without installing them on the system that you are using to download it. Using the normal YUM command downloads the packages and also installs them on your computer. Here is an option that will only download the rpm package for you. It will download it in the folders specified in the '--downloadaddir' option.

```
# yum update httpd -y --downloadonly --downloadaddir=/opt
```

Now, you can install all rpm packages in this folder by running the following command:

```
# rpm -Uivh *.rpm
```

Do remember to run these commands as the root.

—Pratay Modi,
prataymodi@gmail.com

Resolve FSCK failed error

 Sometimes, while booting your Linux system, you may come across the error shown below:

```
FSCK failed. Please repair manually and reboot. The root file
system is currently mounted read-only. To remount it read-write
do:
```

```
bash# mount -n -o remount,rw /
```

Attention: Only CONTROL-D will reboot the system in this
maintenance mode. shutdown or reboot will not work.

Give root password for login: _

Provide your root password and try the following
command:

```
mount -n -o remount,rw /
```

If this does not work for you, reboot your system and do a
manual file system check on your root partition as follows:

```
umount /dev/hddXXX
```

```
fsck -CV /dev/hddXXX
```

...where hddXX is the root partition.

—Abhishek Chib,
abhishek.chib@gmail.com

Undo your changes even after quitting the VIM editor

 As all of us know, if you make changes in a file using VIM editor, the changes are permanent and you cannot get the old version back after you save and quit the editor.

But VIM v7.3 allows you to get the old version back even after quitting the editor.

Here is a tip that shows you how to configure VIM to remember changes.

To enable *Undo*, execute the following commands in VIM just before starting to edit the file.

```
:set undofile
```

```
:set undodir=/tmp
```

This is to be done every time you start editing a file. In case you need the configuration to be there for all files that you open in VIM, create a file called '.exrc' or '.vimrc' in \$HOME directory. In my case, it is /myhome.

Open the just created file and add the following commands:

```
# vi /myhome/.exrc
```

```
set undofile
```

```
set undodir=/tmp
```

Save and close the file.

```
:wq
```

From now onwards, the *Undo* history is maintained in the background for all files that you edit with VIM.

—Adithya Kiran Gangu,
adithya.kiran@gmail.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in LFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get an LFY T-shirt.