



Powered By

facebook

www.facebook.com/linuxforu



Rohit Verma:

Hi all! I had first installed the Windows XP and then Backtrack on my machine. Now it's booting fine but the issue is that before displaying the splash screen it took a time of about 30 seconds, displaying nothing. I am not able to understand how is that time getting wasted. My first boot device is my hard disk from which I am booting both the OS.

Like · comment



Thiya Rajan: For this, you need to edit grub config file, `/boot/grub/grub.conf`. There is a line in there which tells the boot loader which entry in the menu to treat as the default. For time 30 seconds, you can change at `"set timeout=30"`, you can specify the time, based on your need.



Vishnu Revankar:

Can anyone tell me, if I download only the VLC package for RHEL 5.1, would it be good enough for installation or would I need any dependency packages? And apart from VLC, what other media player can be used for RHEL 5.1?

Like · comment



Ashwin Jil: It is simple, you have to install it via rpm `-ivh "vlc or some media player name"`.



Phani Kumar Veluturi: Check this "<http://www.videolan.org/vlc/download-redhat.html>", create a repo file `"/etc/yum.repos.d/vlc.repo"`, after updating `"yum install vlc"`.



Ashwin Jil:

Please help me to fix this error! It occurs whenever I type MySQL in the terminal

ERROR 2002 (HY000): Can't connect to local MySQL server through socket '/var/lib/mysql/mysql.sock' (2)

Like · comment



Phani Kumar Veluturi: MySQL server services are not running, I guess you are updating MySQL server?



Ashwin Jil: Ok thank you, I fixed it by using `init mysqldb start`.



Rajnish Singh:

Can anyone tell me how to connect the Cisco switch (3560) in CentOS.

I had worked with Switch in Windows XP -> hyperterminal. I can't find that hyper terminal in CentOS. I would also like to know how to make cluster in CentOS. I have to make 2 node cluster. Help me please.

Like · comment



Phani Kumar Veluturi: Use minicom or kermi for serial port connection <http://www.howtoforge.com/redhat-cluster-suite-and-conga-linux-cluster-ing> - this is for CentOS 6 version.



Dhiraj Singh:

Hi! How do we mount Windows' drives on Linux (ubuntu 10.10)?

Like · comment



Phani Kumar Veluturi: Here's how to go about it. Type `"sudo apt-get install ntfs-3g"` then `"sudo mount -t ntfs-3g /dev/<windows-partition> /<new-mount_point>"`



Aboobacker Mk: Open the nautilus(file-manager) and double click on the icon of the drive)



Jay Dee: I agree. You should be able to just double-click on it to open; but if it is NTFS, there are some free apps that give you read-write ability.



Parijat Chauhan:

Sadly, the brightness control isn't working on my Vaio. I can't blow Windows unless I can use either Ubuntu, Fedora or OpenSUSE fix the brightness issue for Sony Vaio. Please let me know if there is any way to fix it somehow.

Like · comment



Uday Mittal: Try out this command: `xrandr -output LVDS1 --brightness x` (Where x is the level of brightness you want ranging from .01 to 1)



Parijat Chauhan: Thanks! This worked like a charm!