

```

14     $('button').click(function () {
15         $('div').siblings('caption').each(function() {
16             $(this).children('caption').append("Figure "+
                                                    $(this).
index()+ ": " +
                                                    $(this).
children('pic').attr('alt'));
17         });
18     }); });
19 </script>

20 <body>
21
22 <h4>jQuery Example: Adding figure caption</h4>

23 <div class="section">
24 <p>This example is to generate caption automatically using
jQuery.</p>
25 
26 <div class="caption"></div>
27 </div>

28 <div class="section">
29 <p>This is second picture that we will add caption</p>
30 
31 <div class="caption"></div>
32 </div>

33 <br>
34 <br>
35 <button>Generate figure caption</button>
36 </body>
37 </html>

```

Here, we have:

- **CSS:** Lines 4-10, defining the style for the figure caption in CSS.
- **HTML:** DOM:
 - BODY
 - Heading3
 - DIV (class=section)
 - Paragraph1
 - Picture1 (class=pic)
 - Figure caption (class=caption)
 - DIV (class=section)
 - Paragraph2
 - Picture2 (class=pic)
 - Figure caption (class=caption)
 - button -> to trigger generation of caption

◦ Lines 25 and 30: Note that the 'alt' attribute of the images are descriptive, as the same text will be used as the figure caption.

• jQuery:

- Line 11: Includes the locally available *jquery.js* library.
 - Line 13: Executes the code only after the whole document is loaded and ready. This will ensure the DOM is complete.
 - Line 14: Captures the 'click' event of the button.
 - Line 15: The parent *DIVs* are of class 'section'. The *siblings()* function will select *DIVs* at the same level.
 - The *each()* function lets us perform certain operations on each of these *DIVs*.
 - *\$(this)* refers to the *DIV (section)*, and its children are paragraph, picture and caption.
 - To append the caption text, select the child with the class *caption*.
 - *\$(this).index()* will return the count of selected *DIVs* (section). This is required to find which figure number we are referring to.
 - *\$(this).children('pic')* will select the *IMG* tag. We can extract the 'alt' attribute text using *\$(this).children('pic').attr('alt')*.
- The above example takes you through the key features of jQuery. You can do many more appealing operations, getting to know the other functions provided by the library. For a complete reference, please visit jquery.com.

Extensions for jQuery

This article mainly focused on the jQuery Core library. Two other libraries worth exploring are the jQuery UI and jQuery Mobile. Both are equally popular and widely used. jQuery UI provides many user interface frameworks that have been adopted by websites since a very long time. These frameworks are easily customisable. jQuery Mobile is mainly for interfaces on small-screen devices. The library also takes care of different screen sizes and browsers on different platforms.

jQuery makes programming fun and efficient. Once you start using it, it is tough to go back to doing code from scratch. 

References

- [1] jQuery Home: <http://jquery.com/>
- [2] jQuery Tutorial: <http://www.roseindia.net/ajax/jquery/index.shtml>

By: Janardan Revuru

The author has been working on Web technologies for the last 16 years, developing management software for routers and servers used by enterprise customers. He has worked in the telecom, datacom and high availability domains. He is currently working as a project manager at HP in Whitefield, Bengaluru. He can be reached at janardan.revuru@gmail.com.