

Display the first or last few lines of a file

 To display the first few lines of a file, use the `head` command and `tail` can be used for the last few lines. The command below displays the first `k` lines of the file named `new_file`.

```
$ head -n k new_file
```

Where `k` is an actual integer that denotes the number of lines to be displayed to the standard output.

If the `head` command is used without the `-n` option, it will display the first 10 lines of the file.

Similarly, to display the last '`n`' lines, you can use the `tail` command.

```
$ tail -n k new_name
```

Where `k` is an actual integer that denotes the number of lines to be displayed to the standard output.

This also displays the last 10 lines, if used without the `-n` option.

—Narendra Kangralkar,
narendrakangralkar@gmail.com

Search huge files on your system

 We as users tend to have a quota-based share of HDD space and often run out of it, after which we need to manually search for and delete large unwanted files. Now, here is a simple way to find the big files.

To find files larger than 100 MB, run the following command:

```
find . -type f -size +100M
```

To search for files larger than 1GB and with the extension `.tmp`, run the following command:

```
find . -iname '*.tmp*' -size +1G
```

Here, '+1G' represents more than 1GB.

Similarly, you can type in '-1G', which represents files less than 1 GB. If you do not use the + or - signs, then it searches for files of the exact size – in this case, 1 GB.

You can also include the `-atime` command as shown below to search based on the time accessed:

```
find . -iname '*.tmp*' -size +100M -atime +1
```

The above command will search for files that have been accessed at least a day earlier, with an extension `tmp` with a size larger than 100 MB.

—Pranavam Siddharthan,
pranavam.s@gmail.com

Find recently installed RPM packages

 You must have used the `RPM` command for installing packages. But here is an option by which `RPM` can be used to search recently installed `RPM` packages on your system.

```
rpm -qa --last | less
```

This will list the package name along with the date and time of installation.

—Mohana Sundaram N,
mohan.linux@yahoo.com

Configure wireless or Wi-Fi using the command line

 `iwconfig` is the wireless configuration command used to set basic wireless networking details such as SSID, channel and encryption.

Given below are a few examples that will help you understand and configure your wireless using the following commands.

To display the wireless settings of your interfaces:

```
#iwconfig
```

To set the ESSID (Extended Service Set Identifier) or network name:

```
#iwconfig {interface_name} essid {essid_name}
```

To set the wireless channel of the radio (1-11):

```
#iwconfig {interface_name} {channel}
```

To input a WEP encryption key:

```
#iwconfig {interface_name(e.g.wlan0)} key {key in HEX format}
```

To only allow the adapter to connect to an AP with the MAC address you specify:

```
#iwconfig {interface_name} ap {mac address}
```

—Ajinkya Jiman,
ajinkya.jiman@gmail.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in LFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get an LFY T-shirt.