

```
#stty echo
```

—Suresh Jagtap,
smjagtap@gmail.com

Find more with *find*



Have you ever saved a file, maybe a download, and have then been unable to find it? Maybe you saved it in a different directory or with an unusual name.

Here is a command that will help you search for your lost file.

```
find -type f -mtime 0
```

The output of the above command will show all the files in your home directory modified or created today. By default, *find* counts days from midnight, so an age of zero means today.

You may have used the *-name* option with *find* before, but *find* can do a lot more. These options can be combined together, so if that elusive download was an MP3 file, you could narrow the search with:

```
find -type f -mtime 0 -iname '*.mp3'
```

The quotation marks are needed to stop the shell trying to expand the wildcard, and *-iname* makes the match case-insensitive.

Incorrect permissions can cause obscure errors sometimes. You may, for example, have created a file in your home directory while working as the root. To find files and directories that are not owned by you, use the following command:

```
find ~ ! -user ${USER}
```

The shell sets the environment variable *USER* to the current username, and a *!* reverses the result of the next test, so this command finds anything in the current user's directory that is not owned by that user. You can even use *find* to fix the permissions:

```
find ~ ! -user $USER -exec sudo chown ${USER}:${USER} \;
```

A lot more can be done with *find*. You can go through the man pages for more details.

—Manikandan,
manikandan_vs@yahoo.com

Fun with *xdotool*



xdotool is a command line utility used to play with your X window.

Here are a few examples that make you experience the fun you can have with this tool. If you do not have *xdotool*

already installed, then install it using the package management software of your linux distro. After installing the tool, try the following commands at the terminal.

To move the mouse to 0,0...

```
#xdotool mousemove 0 0
```

To generate left/right clicks...

```
#xdotool click 1  
#xdotool click 3
```

To open the Gnome menu...

```
#xdotool mousemove 0 0; xdotool click 1; xdotool mousemove 10 200
```

Here, you can adjust the value of the mouse-move according to your requirements and menu position.

You can even win the clicking game by running this in an infinite loop. One of my friends got 5200 clicks in 10 seconds. You can try it out and see what you score.

The tool can be used for keyboard controls too. Here is an examples that show how to press Ctrl + ALT + F2 using *xdotool*:

```
#xdotool key ctrl+alt+F2
```

To run a command or launch an application...

Here is an example of how to launch *gedit* using *xdotool*. You can create a script with the following code:

```
xdotool key alt+F2  
WinNum=$(xdotool search 'Run Application')  
xdotool windowfocus $WinNum  
xdotool type gedit  
xdotool key Return
```

To learn more, you can go through the manual pages of *xdotool* or visit <http://www.semicomplete.com/projects/xdotool/>

—Narendra Sisodiya,
narendra@narendrasisodiya.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in LFY so that we can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get an LFY T-shirt.