

with much higher fidelity. This could drastically reduce the reliance on expensive physical wind tunnel testing and lead to aerodynamic designs that significantly cut fuel consumption and emissions.

Energy grid optimisation: As the world shifts towards renewable energy, power grids are becoming increasingly decentralised and complex. Managing the fluctuations of solar and wind energy while balancing supply and demand across millions of nodes is a massive combinatorial optimisation challenge. Quantum annealing and QAOA-based approaches can analyse vast datasets from smart grids in real-time to optimise power flow and storage distribution. By solving these optimisation problems faster than classical solvers, utility companies can prevent blackouts, reduce transmission losses, and integrate a higher percentage of renewables into the grid without compromising stability.

Challenges and limitations of quantum algorithms

Despite the theoretical elegance of quantum algorithms, their practical implementation faces a ‘tyranny of numbers’ where physical constraints currently throttle algorithmic utility. The transition from mathematical proof to industrial advantage is hindered by several formidable barriers.

The decoherence and noise bottleneck (NISQ era constraints): The primary adversary is decoherence, where interaction with the environment causes qubits to lose their quantum state (T1 relaxation and T2 dephasing). Current algorithms must run on Noisy Intermediate-Scale Quantum (NISQ) devices with limited gate fidelity. This restricts ‘circuit depth’—if an algorithm requires too many sequential gates, the signal is drowned out by noise before the calculation concludes.

The massive overhead of Quantum Error Correction (QEC): To run deep algorithms like Shor’s, we need logical qubits that are fault tolerant. However, implementing schemes like the Surface Code requires a massive overhead, potentially needing 1,000 physical qubits to encode just one logical qubit. This means an algorithm requiring 100 logical qubits may demand a processor with 100,000 physical qubits, far beyond today’s hardware capabilities.

The data loading problem (the QRAM challenge): Many algorithms, particularly in quantum machine learning and Grover’s search algorithm, assume we can instantly load classical data into a quantum state. In reality, converting a classical database of size N into a quantum superposition takes $O(N)$ time without efficient quantum RAM (QRAM). This initial loading cost often negates the $O(\sqrt{N})$ speedup gained during the actual search or processing phase.

Limited qubit connectivity and SWAP costs: In many hardware architectures (like superconducting circuits), qubits can only interact with their immediate neighbours. If

an algorithm requires entangling Qubit 1 with Qubit 10, the system must perform a chain of ‘SWAP’ gates to move the information. These SWAP operations add significant depth and noise to the circuit, making complex, highly entangled algorithms difficult to execute faithfully.

The measurement collapse and readout latency:

Quantum algorithms manipulate a vast state space, but we cannot ‘read’ the full state vector; measurement collapses the wave function into a single binary string. To approximate the result distribution, the algorithm must be run thousands of times (‘shots’). This statistical sampling creates a readout bottleneck, making quantum computers slower than classical ones for tasks requiring high-precision scalar outputs.

Verification and debuggability: As we approach ‘quantum supremacy’, we face a paradox: when a quantum computer solves a problem too complex for any classical supercomputer to simulate, how do we verify the answer? Debugging quantum algorithms is notoriously difficult because we cannot inspect the program’s variables (qubit states) in the middle of the execution without destroying the computation, forcing researchers to rely on indirect verification methods.

Quantum algorithms represent a leap forward in computational capability, offering solutions to problems once thought insurmountable. Shor’s and Grover’s algorithms have paved the way for a new era, inspiring advances in optimisation, simulation, and machine learning. While challenges remain, continued innovation in quantum algorithm design and hardware development promises to unlock new possibilities for science and industry. **END** 🐼

References

- <https://www.quantum-inspire.com/kbase/what-is-a-quantum-algorithm/>
- <https://quantum.microsoft.com/en-us/insights/education/concepts/quantum-algorithms>
- <https://www.geeksforgeeks.org/dsa/introduction-to-grovers-algorithm/>
- <https://www.quantum-inspire.com/kbase/grover-algorithm/>
- <https://pennylane.ai/qml/whatisqml>
- <https://www.spinquantum.com/news-detail/what-is-a-quantum-computer-used-for>

By: Dr Magesh Kasthuri and Dr Anand Nayyar

Dr Magesh Kasthuri is a PhD in artificial intelligence and the genetic algorithm. He currently works as a distinguished member of the technical staff (master) and chief architect at Wipro Ltd. This article expresses his views and not of the organisation he works in.

Dr Anand Nayyar is a PhD in wireless sensor networks and swarm intelligence. He works at Duy Tan University, Vietnam, and loves to explore open source technologies, IoT, cloud computing, deep learning, and cyber security.