

```
> str_to_sentence(t)
[1] "R, statistics and machine learning"
```

str_count

You can count the number of occurrences of a character in a string with the `str_count()` function. The syntax usage is as follows:

```
str_count(string, pattern = "")
```

A couple of examples are given below for reference:

```
> str_count(t, "a")
[1] 4

> str_count(t, c("a", "e"))
[1] 4 2
```

str_dup

You can duplicate a string with the `str_dup()` function, which accepts an input string and a number for replication. The number of times for duplication can also be a list as shown below:

```
> str_dup(t, 1)
[1] "R, Statistics and Machine Learning"

> str_dup(t, 2)
[1] "R, Statistics and Machine LearningR, Statistics and Machine Learning"

> str_dup(t, 1:3)
[1] "R, Statistics and Machine Learning"
[2] "R, Statistics and Machine LearningR, Statistics and Machine Learning"
[3] "R, Statistics and Machine LearningR, Statistics and Machine LearningR, Statistics and Machine Learning"
```

str_detect

The `str_detect()` function returns a TRUE Boolean value if the pattern match exists in the given input string, and FALSE otherwise. You can use the `regex()` syntax for specific patterns for a match. The negate argument, if set to TRUE, can return non-matching elements. Examples to demonstrate this function are given below:

```
> str_detect(t, "a")
[1] TRUE

> str_detect(t, "[ae]")
[1] TRUE

> str_detect(t, "^s")
```

```
[1] FALSE
```

```
> str_detect(t, "g$")
[1] TRUE
str_conv
```

The `str_conv()` function can help convert the encoding of a string from the default format. The syntax usage is as follows:

```
str_conv(string, encoding)
```

Examples that use the ISO-8859-1 encoding are given below for reference:

```
> str_conv("\xa9", "ISO-8859-1")
[1] "©"

> str_conv("\xbc", "ISO-8859-1")
[1] "¼"

> str_conv("\xbd", "ISO-8859-1")
[1] "½"

> str_conv("\xbe", "ISO-8859-1")
[1] "¾"
```

str_equal

You can compare if two strings are equal using the Unicode rules with the `str_equal()` function. It accepts the following arguments:

Argument	Description
x	A character vector
y	Another character vector
locale	'en' for English
ignore_case	Boolean value to ignore case

A couple of examples are shown below:

```
> str_equal("hello", "hi")
[1] FALSE

> str_equal("\u1342", "\u1342")
[1] TRUE
```

str_like

The pattern matching for a string for the SQL LIKE operator syntax is implemented with the `str_like()` function. The syntax usage is as follows: