

Argument	Description
x	Character vector
decreasing	TRUE for highest to lowest FALSE otherwise (default)
na_last	Boolean to handle NA values
numeric	Sort digits numerically

A couple of examples are given below:

```
> str_sort(vowels)
[1] "a" "e" "i" "o" "u"

> f <- c("beta", "alpha", "gamma", "delta")

> str_sort(f)
[1] "alpha" "beta" "delta" "gamma"
```

str_remove

The *str_remove()* function removes text that matches a pattern for an input string. It accepts two arguments — an input vector string, and a pattern. An example of the use of this function is given below:

```
> str_remove(t, "\\s")
[1] "R,Statistics and Machine Learning"

> str_remove(t, "[aeiou]")
[1] "R, Sttistics and Machine Learning"
```

str_replace

The *str_replace()* function replaces the first occurrence of the pattern with the replacement string. The syntax usage is as follows:

```
str_replace(string, pattern, replacement)
```

A couple of examples are as follows:

```
> str_replace(t, "\\s", "-")
[1] "R,-Statistics and Machine Learning"

> str_replace(t, "[aeiou]", " ")
[1] "R, St tistics and Machine Learning"
```

str_split

You can split a string into multiple segments using the *str_split()* function. It has multiple options.

The *str_split()* accepts a character vector and returns a list as shown below:

```
> str_split(t, " ")
[[1]]
[1] "R," "Statistics" "and" "Machine"
"Learning"
```

The *str_split_1()* uses a single string and returns a character vector. For example:

```
> str_split_1(t, "and")
[1] "R, Statistics" "Machine Learning"
```

The *str_split_fixed()* accepts a character vector and returns a matrix of values. A couple of examples are given below:

```
> str_split_fixed(t, " ", 2)
[,1] [,2]
[1,] "R," "Statistics and Machine Learning"
```

```
> str_split_fixed(t, " ", 3)
[,1] [,2] [,3]
[1,] "R," "Statistics" "and Machine Learning"
```

The *str_split_i()* takes a character vector and returns a character vector. A few examples are given below to demonstrate this function:

```
> str_split_i(t, " ", 1)
[1] "R,"

> str_split_i(t, " ", 2)
[1] "Statistics"

> str_split_i(t, " ", 3)
[1] "and"
```

You are encouraged to read the *stringr* reference manual to learn more about its functions, arguments, options, and usage. 

References

- stringr GitHub, <https://github.com/tidyverse/stringr>
- stringr home page, <https://stringr.tidyverse.org/>

By: Shakthi Kannan

The author is a free software enthusiast.