

```
=> => transferring context: 78B
0.0s
=> [1/2] FROM docker.io/library/openjdk:11.0-jdk-slim@sha
256:868a4f2151d38ba6a09870cec584346a5edc8e9b71fde275eb2e06
25273e2fd8 119.2s
=> => resolve docker.io/library/openjdk:11.0-jdk-slim@sha
256:868a4f2151d38ba6a09870cec584346a5edc8e9b71fde275eb2e06
25273e2fd8 0.0s
=> => sha256:868a4f2151d38ba6a09870cec584346
a5edc8e9b71fde275eb2e0625273e2fd8 549B / 549B
0.0s
=> => sha256:d2b6af2093e823ba0cdee4bcd45a905af
e3fa054d08bde55b1d850515da69a08 1.16kB / 1.16kB
0.0s

=> => sha256:8e687a82603fe2a40c7c83684fc5b97b7
5dd4d51ce6b0e6250ef3fd64b7b9f66 5.59kB / 5.59kB
0.0s

=> => sha256:1efc276f4ff952c055dea726cfc96ec6a4
fdb8b62d9eed816bd2b788f2860ad7 31.37MB / 31.37MB
53.1s

=> => sha256:a2f2f93da48276873890ac821b3c991d5
3a7e864791aaf82c39b7863c908b93b 1.58MB / 1.58MB
4.7s
=> => sha256:12cca292b13cb58fadde25af113ddc4ac3b0c5e39ab3
f1290a6ba62ec8237afd 212B / 212B 0.2s

=> => sha256:69e15dccc787ba2cfe67f6abf5970ed88a5e019efbb4
99e499da3ab20b85fcc7 202.34MB / 202.34MB 117.6s

=> => extracting sha256:1efc276f4ff952c055dea726cfc96ec6a
4fdb8b62d9eed816bd2b788f2860ad7 2.0s
=> => extracting sha256:a2f2f93da48276873890ac821b3c991d5
3a7e864791aaf82c39b7863c908b93b 0.2s

=> => extracting sha256:12cca292b13cb58fadde25af113ddc4ac
3b0c5e39ab3f1290a6ba62ec8237afd 0.0s

=> => extracting sha256:69e15dccc787ba2cfe67f6abf5970ed88
a5e019efbb499e499da3ab20b85fcc7 1.6s
=> [2/2] COPY target/my-app-1.0-SNAPSHOT.jar app.jar
0.2s
=> exporting to image
0.0s
=> => exporting layers
0.0s
=> => writing image sha256:40ac0922ea5a75a65b048826
2b66f10e702130633c60bab17d5b798aefff37ab 0.0s
```

```
=> => naming to docker.io/library/my-app:latest
```

Verify existing Docker images:

```
test@ubuntu:~/Desktop/my-app$ sudo docker images
```

REPOSITORY	TAG	IMAGE ID	CREATED	SIZE
my-app	latest	937b0c334197	11 seconds ago	654MB
nginx	latest	a6bd71f48f68	2 weeks ago	187MB

Let's start a container from the image that we created.

```
test@ubuntu:~/Desktop/my-app$ sudo docker run my-app:latest
Hello World!
```

Verify existing Docker containers:

```
test@ubuntu:~/Desktop/my-app$ sudo docker ps -a
```

In the next section, we will push the Docker image to DockerHub.

Pushing Docker image to DockerHub

Use the *docker login* command from the terminal to login to the DockerHub account of testUser.

Tag the image:

```
test@ubuntu:~/Downloads$ sudo docker tag 40ac0922ea5a
testUser/my-app
```

Now use the *docker push* command using the same tag:

```
test@ubuntu:~/Downloads$ sudo docker push testUser/my-app
Using default tag: latest
The push refers to repository [docker.io/testUser/my-app]
7c25c686d66b: Pushed
eb6ee5b9581f: Mounted from library/openjdk
e3abdc2e9252: Mounted from library/openjdk
eafe6e032dbd: Mounted from library/openjdk
92a4e8a3140f: Mounted from library/openjdk
latest: digest: sha256:b77631855b956abe6011f9468cd8947708638c
ee63f2474fbbb95d7056ac0859 size: 1368
```

The job is done!

You have now learnt how to deploy a Java-based app on Docker. I do hope you found this tutorial informative and easy to follow. 

 By: Mitesh Soni

The author believes in the power of open source, and has more than 10 years of experience in research and innovation.