

```

apiVersion: kustomize.config.k8s.io/v1beta1
kind: Kustomization
resources:
  # Find the latest tag here: https://github.com/ansible/awx-operator/releases
  - github.com/ansible/awx-operator/config/default?ref=1.1.4
  # Add this extra line:
  - awx-demo.yaml

# Set the image tags to match the git version from above
images:
  - name: quay.io/ansible/awx-ee:21.11.0
    newTag: 1.1.4

# Specify a custom namespace in which to install AWX
namespace: awx

```

Figure 1: *kustomization.yaml* file

- By executing the following command we can verify whether Kubernetes has started some pods or not:

```
minikube kubectl -- get pods -A
```

We do not need to install kubectl separately since it is already wrapped inside a minikube.

- Once Kubernetes starts making pods, let's create an alias for easier usage using the following command:

```
alias kubectl="minikube kubectl --"
```

- When our Kubernetes cluster starts running, we can deploy AWX Operator in our cluster using Kustomize, which is a Kubernetes configuration transformation tool. To install Kustomize by downloading precompiled binaries use the command given below:

```
curl -s "https://raw.githubusercontent.com/kubernetes-sigs/kustomize/master/hack/install_kustomize.sh" | bash
```

- Confirm the installation of Kustomize by checking the version using the following command:

```
kustomize version
```

- Next, create a file called *kustomization.yaml*, which has the content shown in Figure 1.

In place of *newTag* and *ref* we can pass the latest version of AWX Operator, which can be found at <https://github.com/ansible/awx-operator/releases>. Here, we are using AWX Operator version 1.1.4. We can also save the latest version from AWX Operator releases as *RELEASE_TAG* variable, and pass that variable instead of passing the hardcoded latest

AWX Operator version.

The AWX Operator is used to manage one or more AWX instances in any name space within the cluster.

- Now, we have to install the manifests by running the following command:

```
kustomize build . | kubectl apply -f -
```

- Wait for a few minutes and check if the AWX operator is deployed or not by using the command:

```
kubectl get pods -n awx
```

If the status shows *Running*, it means our operator has been deployed successfully.

- Since we would rather not keep repeating *-n awx*, we should set the current name space for *kubectl* using the command given below:

```
kubectl config set-context --current --namespace=awx
```

- Now create another file named *awx-demo.yaml* in the

```

apiVersion: awx.ansible.com/v1beta1
kind: AWX
metadata:
  name: awx-demo
spec:
  service_type: nodeport
  # default nodeport_port is 30080
  nodeport_port: <nodeport_port>

```

Figure 2: *awx-demo.yaml* file