

The above command will display all the machines that are live and responding to port 22, with an IP address within the range 192.168.1.1 - 255

—Kaushik Debnath,
caesar431@gmail.com



Check your disk space usage

In Linux, you can view summaries of your disk space usage from the command line. Follow the steps shown below.

Step 1: Open the terminal, and enter the following command:

```
du -sb path
```

...where,
-s specifies the summaries
-b specifies the print sizes in bytes
path specifies the path of your folder or the location of your directory.

Example:

```
#du -sb /home/yourdirectory
```

You can also find the disk usage in GB, MB and KB.

Here are the commands for viewing the output in different units.

For disk usage in KB:

```
du -sk /path
```

For disk usage in MB:

```
du -sm /path
```

For disk usage in GB:

```
du -sh /path
```

If you use '-c' options, it returns the grand total of all the arguments after they have all been processed. This can be used to find out the disk usage of the directory.

—Mahabaleshwara Adiga,
adigamca@gmail.com



Printing the gcc predefined macros to stdout

Here is a tip that will let you know the list of gcc-used macros and their values. The commands to use are shown below:

```
touch foo.h  
gcc -dM -E foo.h
```

Executing the above commands will list all the macros used.

The option:

-dM will generate the list of all #defines used by the pre-processor during execution, which also includes pre-defined macros.

-E will stop the compiler after the pre-processing stage. It will not enter the compiling stage. The output will be in the preprocessed form and will be sent to stdout.

—Yogindar Das Y,
yogindar@yahoo.com



Capture all your activities

The tip shared here will help developers as well as general-purpose Linux users. It will allow you to save a remote syslog automatically to the local disk without doing a scp or cp, save all your terminal activities automatically to the local disk, recall a forgotten command and trace back what commands you run on your system to debug a specific problem. So let's look at all that needs to be done.

First, create a directory named *termOutput* in your home directory and then create a file called *termOutput/sessionId* with the initial value 0.

Now create a directory named *bin* in your home directory and create an executable script under *bin* called *captureScreen* with the following code in it:

```
#!/bin/bash  
currSessionId=`cat ~/termOutput/sessionId`  
currSessionId=$((currSessionId+1))  
echo "Session Id is.." $currSessionId  
echo $currSessionId > ~/termOutput/sessionId  
script -a ~/termOutput/$currSessionId.out
```

Any terminal application that you use (like GNOME terminal) must have a setting for a profile. At the GNOME terminal, go to *Edit --> Profile preferences --> Title and Command --> Command*. Check the option *Run a custom command instead of my shell* and put the complete path of the above script.

Now, the next time you open a terminal, you will see something like what's shown below:

```
Session Id is.. 537  
Script started, file is ~/termOutput/537.out  
xyz@xyz:~$
```

Whenever you want to find something, you can always go back to these saved files to search for what you want.

—Madhusudana Y N,
madhusudanayn@gmail.com

END -

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in OSFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get a T-shirt.