

Field	Type	Null	Key	Default	Extra
student_id	int(5)	NO	PRI	NULL	auto_increment
name	varchar(20)	YES		NULL	
age	int(5)	YES		NULL	
marks	int(5)	YES		NULL	

Figure 3: A sample table created

Creating a database in MariaDB

When entering the account administrator password set up during installation, you will be given a MariaDB prompt.

Create a database on students by using the following command:

```
CREATE DATABASE students;
```

Switch to the new database using the following command (this is to make sure that you are currently working on this database):

```
USE students;
```

Now that the database has been created, create a table:

```
CREATE TABLE details(student_id int(5) NOT NULL AUTO_INCREMENT,
                        name varchar(20) DEFAULT NULL,
                        age int(3) DEFAULT NULL,
                        marks int(5) DEFAULT NULL,
                        PRIMARY KEY(student_id)
);
```

To see what we have done, use the following command:

```
show columns in details;
```

Each column in the table creation command is separated by a comma and is in the following format:

```
Column_Name Data_Type([size_of_data]) [NULL or NOT NULL]
[DEFAULT default_value]
[AUTO_INCREMENT]
```

These columns can be defined as:

- **Column Name:** Describes the attribute being assigned.
- **Data Type:** Specifies the type of data in the column.
- **Null:** Defines whether null is a valid value for that field — it can be 'null' or 'not null'.
- **Default Value:** Sets the initial value of all newly created records that do not specify a value.
- **auto_increment:** MySQL will handle the sequential numbering of any column marked with this option, internally, in order to provide a unique value for each record.

Ultimately, before closing the table definition, we need to use the primary key by typing **PRIMARY KEY(column name)**. It guarantees that this column will serve as a unique field.

student_id	name	age	marks
1	anu	15	450
2	Bob	15	400

2 rows in set (0.00 sec)

Figure 4: Inserting data into a table

Inserting data into a MariaDB table

To insert data into a MariaDB table, use the following commands:

```
INSERT INTO details(name,age,marks) values ("anu",15,450);
```

```
INSERT INTO details(name,age,marks) VALUES("Bob",15,400);
```

The output will be as shown in Figure 4.

We need not add values in *student_id*. It is automatically incremented. All other values are given in quotes.

Deleting a table

To delete a table, type the following command:

```
DROP TABLE table_name;
```

Once the table is deleted, the data inside it cannot be recovered.

We can view the current table using the **show tables** command, which gives all the tables inside the database:

```
SHOW tables;
```

After deleting the table, use the following commands:

```
DROP TABLE details;
Query OK, 0 rows affected (0.02 sec)
```

```
SHOW tables;
```

The output will be:

```
Empty set (0.00 sec)
```

Google waves goodbye to MySQL

Google has now switched to MariaDB and dumped MySQL. "For the Web community, Google's big move might be a paradigm shift in the DBMS ecosystem," said a Google engineer. Major Linux distributions, like Red Hat and SUSE, and well-known websites such as Wikipedia, have also switched from MySQL to MariaDB. This is a great blow to MySQL.

Google has migrated applications that were previously