

Event designators for history

Consider the history log for the upcoming event designator examples:

```
[bash]$ history

1  pwd
2  ls
3  cd Documents/
4  ll
5  nautilus
6  history

!n
```

The above executes command number 'n'.

```
[bash]$ !1

pwd

/home/christmas/Documents

!-n
```

This executes current command minus 'n'.

```
[bash]$ !-3

total 1648

drwxr-xr-x  5 christmas christmas 4096 Nov  6 11:48 ./
drwxr-xr-x 35 christmas christmas 4096 Nov  8 18:34 ../
-rw-rw-r--  1 christmas christmas 8164 Nov  4 19:05 24914.png
-rw-rw-r--  1 christmas christmas 27817 Nov  5 12:05
400_F_37625904_mN1lKUnYH3cnVRKPlankmHzcz1zw1SjN.jpg

!!
```

This executes the previous command. This is similar to '!-1'.

```
[bash]$ !!

1  pwd

2  ls
```

```
3  cd Documents/
4  ll
5  nautilus
6  history

!string
```

...executes the most recent command preceding the current position in the history list, starting with the specified string.

```
[bash]$ !pw

pwd

/home

^string1^string2^
```

Quick substitution is of the form *^original^replacement^*. Repeat the last command, replacing the *original* with the *replacement*.

```
[bash]$ cd documents

bash: cd: documents: No such file or directory

[bash]$ ^documents^Documents^

cd Documents

[bash]$

Ctrl+r
```

Pressing *Ctrl+r* from the command prompt will display the *reverse-i-search* prompt as shown below.

Search previously executed commands with the *Ctrl+r* command. Once you've found the command you're looking for, press *Enter* to execute it.

```
[bash]$ cat test

This is a test file.

(reverse-i-search)'test': cat test [Enter]

[bash]$ cat test

This is a test file.
```