



TIPS & TRICKS



Comment specific lines in VI editor

Here is how we can comment a specific line in a file using a VI editor.

The syntax is:

```
:x,y s/^/#/g
```

Here,

x,y: The starting and ending line number

^: This points to the start of the line

#: The usual way to comment in config files in Linux

As an example, open a config file in VI Editor and run the following command:

```
:450,500 s/^/#/g
```

This will comment lines numbered 450 to 500 in the opened file:

```
!.,+10 s/^/#/g
```

Here, '.' is the current line and '+10' refers to ten lines from the current one.

—Ranjith Kumar,
ranjith.stc@gmail.com



Create a logical swap from a normal swap file

First, check the swap device:

```
#cat /proc/swaps [ex: given below]
```

Filename	Type	Size	Used	Priority
/dev/sda2	partition	4095992	0	-1

Then, **swapoff** the device:

```
#swapoff /dev/sda2
```

Create PV, VG and LV:

```
#pvcreate /dev/sda2
```

WARNING: swap signature detected on /dev/sda2. Wipe it?
[y/n] - type Y

Create **New_VG** or assume that **VG{New_VG}** already is in the system, so just extend it:

```
#vgextend New_VG /dev/sda2
```

You can check the **vg** using the command below:

```
#vgsdisplay
```

Let's assume that we are going to create a 2 GB logical swap:

```
#lvcreate -L 2G -n lvSwap New_VG
```

Now you can use the following command to see **lvswap**:

```
#lvsdisplay
```

To make this as a swap partition, use the following command:

```
#mkswap /dev/New_VG/lvSwap
```

Here, the device name is the same as what we got as an output from **lvdisplay** command.

It will show you the setting up version of the **swap**space with the size and some other information.

Finally, to complete the process **swapon** the **lv** device as shown below:

```
#swapon /dev/New_VG/lvSwap
```

To make these changes permanent, change the swap entry in **/etc/fstab** by adding the following line: