

[illegible]

Figure 3: Deployment messages

[illegible]

Figure 4: Buster generating static files

```
git add file_name_to_be_added
git commit -m "Commit Message"
git push origin master
```

```
rhc app restart ghost # Replace ghost with the name of app
```

After this, you will see something similar to what is shown in Figure 3.

Github pages

GitHub provides an excellent service to serve static pages. But Ghost requires *node.js* on the server side, so let's look at a workaround. The solution lies in Buster, a brute force static site generator for Ghost. Buster can be pointed at any Ghost blog—a blog hosted on an external website or one running locally on your own computer—and output a directory with the static content of the site. Before this, create a repo on GitHub with the name *username.github.io* (replace *username* with your GitHub username) if you don't have one already. If you already have a

site live on Github and you don't want to alter it, make a new repo and name it 'ghost', and it will be available at *username.github.io/ghost*. Installing Buster is easy; just issue the following command:

```
pip install buster # prefix with sudo, if following
command fails
```

Also make sure you have `wget` installed. To store the static content, create a separate folder for proper management, which I will name as `buster_files`:

```
mkdir buster_files
cd buster_files
```

From the folder, run the following command:

buster setup

...and enter the address of the Github repo you created above. In my case, I was deploying to a repo named *ghost*, so it was <https://github.com/jatindhankhar/ghost.git>. Once you are done with this, run the following code:

```
buster generate -- domain=http://127.0.0.1:2368 # If
ghost is running locally
# or if you already have a ghost running somewhere else,
use
buster generate - domain=http://address-to.ghost.blog
# Run it only on the ghost you own, otherwise you may
violate some data mining laws
```

After Buster is done, it will store all the files in a folder named *static*. Switch to the *static* folder and *add*, *commit* and *push* the files to the repo using Git.

```
cd static
git add.
git commit -m "Your commit message here"
git push origin gh-pages
```

If you have some money to spare, I would recommend that you go in for hosted ghost blogs. **END** 

References

- [1] <http://docs.ghost.org/>
- [2] <https://ledtechnica.com/free-ghost-hosting-on-github-pages/>
- [3] <https://github.com/axitkhurana/buster>
- [4] <http://ghost-chops.rhcloud.com/hosting-ghost-on-openshift/>

By: Jatin Dhankhar

The author, who is currently doing his B. Tech in computer science from Ramanujan College, University of Delhi, is crazy about computers and loves to learn about anything related to them. He can be reached at jatin@jatinthankhar.in