



Search man pages with these commands

Here are a few commands that can come handy while searching through man pages in Linux.

```
$man -k ssh
```

The above command will show all available commands that contain the word `ssh` in their description.

Also, if you need to check short descriptions of the command, you can use the following:

```
$whatis ssh
```

Or:

```
$man -f ssh
```

—Somnath Sarode,
somnathsarode@gmail.com



ispell: A spell check for UNIX

This is a program used to perform a very basic spell check from the command line. Here is a tip that lets you know how to use `ispell`.

First, install it if it's not already installed, by running the following command:

```
#sudo apt-get install aspell aspell-en
```

Now, to see `ispell` in action, run the command shown below:

```
#ispell <filename>
```

You now have the option of several actions that you can take on misspelled words found in the file.

Type the number 'n' to replace the misspelled word.

Type 'R' to replace the misspelled word with a word that you wish to replace it with.

Press 'A' to ignore that misspelled word in this entire `ispell` session.

Press 'Q' to quit the program.

Press the space bar to ignore that misspelled word just once.

Press 'I' to ignore all the misspelled words.

—Pankaj Rane,
pankaj.rane2k8@gmail.com

Find user accounts without passwords

Open a terminal window and enter the following command, which will display all user accounts without passwords:

```
#awk -F: '{($2 == "") {print}}' /etc/shadow
```

—Suresh Jagtap,
smjagtap@gmail.com



Gaining remote access using ssh on a specific port

To connect to a remote Linux system, we often use `ssh`, which is a program for logging into a remote machine and executing commands on it. By default, `ssh` uses Port Number 22 to communicate. Here is a tip that lets you connect to the server with `ssh` without using the default port.

```
#ssh -p port-number root@host-name
```

—Baranitharan Krishnamoorthy,
baraninandhu@gmail.com



Unmount that stubborn USB device

I often encounter a peculiar and irritating problem with pen drives and USB storage devices. I am not able to eject/unmount these devices, and get the error message: 'The device is busy.' One simple solution is to run the command `sync` to flush out incomplete buffers, and then run:

```
$sudo umount
```

There are, of course, more sophisticated methods, but try this simple solution first to resolve this irritating problem.

—Dr Parthasarathy S,
drpartha@gmail.com