



Force file system check during the next reboot

Here is a method that allows you to force a Linux-based system to run the `fsck` command on the next boot of the system. `fsck` is used to check and optionally repair one or more Linux file systems.

To run this forcibly, go to the root directory and create a file named 'forcefsck' as shown below:

```
#cd /  
  
#touch forcefsck
```

The file `forcefsck` will be deleted automatically after `fsck` is finished.

This will only run the full file system check on the next reboot of the system.

—Munish Kumar,
munishtotech@gmail.com



Know your CPU

Running the following command on the terminal can give you the entire details of the CPU being used in your system:

```
#lscpu
```

—Rahul Mahale,
rahul.mahale123@gmail.com



Access the Windows desktop

There is a powerful utility (command) on Linux to access the remote desktop of any Windows system. The `rdesktop` is found already installed in many Debian-based systems. If not, it can be installed by running the following command:

```
$sudo apt-get install rdesktop
```

It uses Remote Desktop Protocol (RDP) for remote access. In order to access any Windows desktop, go to the terminal and type the following command:

```
rdesktop ip-address -u username -p password
```

For example:

```
$rdesktop 172.16.1.1 -u ajintha -p AUrAngAbAd
```

It will log on to the Windows system in the network that has the following IP address: 172.16.1.1, with the username `ajintha` and password `AUrAngAbAd`. It will show the Windows desktop of this system. Now, you can operate this Windows system from your Linux system!

—Tushar Kute,
tushar@tusharkute.com



Installing .bin files in Linux

We often download software as an execute file

with the extension `.bin` and then do not know how to install it. Here are a few steps that will let you run the `.bin` file in Linux.

First, change the file mode bits of the downloaded `.bin` file using the following command:

```
$cd /path/to/your/bin  
$sudo chmod a+x <yourbinfile>.bin
```

Now run the executable by using `./`

```
./<yourbinfile>.bin
```

—Kiran P S,
pskirann@gmail.com



Delete specific commands from History

Use the 'up' arrow to browse through the history of commands that have been used in the terminal and go to the command you want to delete. For example:

```
#cat /etc/passwd
```

Now press `Ctrl+u`

This will delete the selected command from `History`.

To check if it is deleted or not, run the following command:

```
#history
```

The output of the above command will show a blank with the `*` symbol in place of the deleted command.

—Naresh Kumar,
nrshvn@gmail.com



Finding the biggest files in Linux

Here is a command that will help you find the biggest files in the current directory:

```
$ls -lSr
```

The 'r' causes the large files to be listed at the end, and the 'h' gives human readable output.

—Munish Kumar,
munishtotech@gmail.com

END

Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.linuxforu.com. The sender of each published tip will get a T-shirt.