



Tyrone®

a solution **flexible** enough to adapt to your **requirements**

OPSLAG FS2

SPECIFICATION

Flexible Host Interface

Supports Gigabit Ethernet, 10GB Ethernet, FC, SDR/DDR/QDR (10Gbps/20Gbps/40Gbps) as individual connectivity or in combination

Scalable Storage

Supports up to PetaByte from few TB's using Tyrone expandable solutions

Redundancy/Fault-tolerance

Power-Supply, Host interface failover, RAID 6(various level of RAID supported), Multiple Snapshots with scheduling, Volume/Share Replication, Remote Replication (Block level replication to a 2nd unit with failover/high availability)

Supports Virtual Tape Library

iSCSI target, Fibre-Channel target, SRP target

- UP To 2Giga Bytes/sec
- UP To PetaByte
- SRP Support



Flexible Host Interface



Redundancy Fault-Tolerance



FS2



Scalable Storage



VTL
Supports Virtual Tape Library



New Delhi - Bangalore - Mumbai - Hyderabad - Chennai

Netweb
TECHNOLOGIES
ISO 9001:2000 Company

Corporate Office, B-1/A25, 2nd Floor, Mohan Co-Operative Industrial Estate
Mathura Road, New Delhi - 110044

www.netwebindia.com | www.tyronesystems.com
info@netwebindia.com | netweb@vsnl.com

Tyrone System Inc. Specifications subject to change without notice. Intel, The Intel Logo, Xeon, and Xeon Inside are trademarks or registered trademarks of Intel Corporation in the U.S. and/or other countries. All other brands and names are the property of their respective owners.