

```
upstart dist 10gen' | sudo tee /etc/apt/sources.list.d/
mongodb.list
```

- Reload the local package database:

```
sudo apt-get update
```

- Install the MongoDB packages:

```
sudo apt-get install mongodb-org
```

Debian

- Import the public key used by the package management system:

```
sudo apt-key adv --keyserver hkp://keyserver.ubuntu.com:80
--recv 7F0CEB10
```

Create the `/etc/apt/sources.list.d/mongodb.list` list file using the following command:

```
echo 'deb http://downloads-distro.mongodb.org/repo/ubuntu-
upstart dist 10gen' | sudo tee /etc/apt/sources.list.d/
mongodb.list
```

- Reload the local package database:

```
sudo apt-get update
```

- Install the MongoDB packages:

```
sudo apt-get install mongodb-org
```

Getting started with MongoDB

From a system prompt, start MongoDB by running the 'mongo' command, as follows:

```
mongo
```

Select a database

From the Mongo shell, display the list of databases, with the following operation:

```
show dbs
```

Switch to a new database named `mydb`, with the following operation:

```
use mydb
```



Note: If 'mydb' is not present, a database with the name 'mydb' will be created.

Confirm that your session has the `mydb` database as context, by checking the value of the `db` object, which returns the name of the current database, as follows:

```
Db
```

Create a collection and insert documents

A collection can be created and documents can be inserted by the following methods.

Using Python PyMongo:

Install PyMongo

```
sudo pip install pymongo
```

```
python
```

```
>>>import pymongo
>>> client = MongoClient()
>>> db = client.test_database
>>> collection = db.test_collection
>>> db.test_database.insert({'i': i} for i in
xrange(10000)))
```

Directly from the Mongo shell:

```
for (var i = 1; i <= 25; i++) db.testData.insert( { x : i } )
```

```
or
```

```
j = { name : "mongo" }
k = { x : 3 }
db.testData.insert( j )
db.testData.insert( k )
```

Display collections

```
show collections
```

Or...

```
db.getCollectionNames()
```

MongoDB replication

In order to replicate the database, the following steps may be taken:

- Edit the `/etc/mongodb.conf` on all the servers and add the following commands:

```
replSet=<Replication set name>
rest=true
```

- Start `mongod` with `mongod.conf`:

```
mongod -f /etc/mongodb.conf
```