



Figure 1: Working dfs format



Figure 2: HDP namenode and datanode

```
<configuration>
<property>
<name>dfs.replication</name>
<value>1</value>
</property>
<property>
<name>dfs.namenode.name.dir</name>
<value>file:/hdp/data/dfs/namenode</value>
</property>
<property>
<name>dfs.datanode.data.dir</name>
<value>file:/hdp/data/dfs/datanode</value>
</property>
</configuration>
```

Edit or create the file `C:\hdp\etc\hadoop\slaves`. (This file lists the hosts, one per line, where the Hadoop slave daemon's datanode and tasktrackers will run. By default, this contains the single entry `localhost`.) Make sure it has the following entry:

localhost

Edit or create `C:\hdp\etc\hadoop\mapred-site.xml` (contains the framework for executing MapReduce jobs) and add the following entries:

```
<configuration>
<property>
<name>mapreduce.framework.name</name>
<value>yarn</value>
</property>
</configuration>
```

Finally, edit or create *yarn-site.xml* and add the following entries:

```
<configuration>
<property>
<name>yarn.nodemanager.aux-services</name>
<value>mapreduce_shuffle</value>
</property>
<property>
<name>yarn.nodemanager.aux-services.mapreduce_shuffle.class</name>
<value>org.apache.hadoop.mapred.ShuffleHandler</value>
</property>
<property>
<name>yarn.application.classpath</name>
<value>
%HADOOP_HOME%\etc\hadoop,
%HADOOP_HOME%\share\hadoop\common\*,
%HADOOP_HOME%\share\hadoop\common\lib\*,
%HADOOP_HOME%\share\hadoop\mapreduce\*,
%HADOOP_HOME%\share\hadoop\mapreduce\lib\*,
%HADOOP_HOME%\share\hadoop\hdfs\*,
%HADOOP_HOME%\share\hadoop\hdfs\lib\*,
%HADOOP_HOME%\share\hadoop\yarn\*,
%HADOOP_HOME%\share\hadoop\yarn\lib\*
</value>
</property>
</configuration>
```

Initialising environment variables

Once all four files are configured, run *hadoop-env.cmd* and format the namenode file system. Run the following command prompt:

```
C:\hdp\etc\hadoop>hadoop-env.cmd
```

```
C:\hdp\etc\hadoop>C:\hdp\bin\hdfs namenode -format
```