

Configure Glassfish on a Clustered Environment

Discover how to install and configure the Glassfish application server clustered environment on Red Hat Enterprise Linux Server 6.1.



Glassfish is a free and open source application server rolled out by Sun Microsystems for the Java EE platform, and is now sponsored by the Oracle Corporation. Using Glassfish, one can create enterprise applications that are both portable and scalable. This article continues from where the earlier write-up 'An Introduction to Glassfish: The Enterprise Application Server' left off.

Before proceeding with the installation, let us ensure that we are equipped with the following prerequisites:

- Two servers are prepared with OS RHEL6.1. The hostname and IP address used are:
 First node GF-Node01 192.168.10.10
 Second node GF-Node02 192.168.10.11
- Each server's '/etc/hosts' configuration file should contain the details of both the servers. It should look as shown below:

```
#cat /etc/hosts
```

```
127.0.0.1 localhost localhost.localdomain localhost4
localhost4.localhost4
::1 localhost localhost.localdomain localhost6 localhost6.
localhost6
192.168.10.10 GF-Node01.rsys.org GF-Node01
192.168.10.11 GF-Node02.rsys.org GF-Node02
```

- Set the IP address as follows:
[System -> Preferences -> Network Connection]

- Turn off the firewall as follows:
[System -> Administration -> Firewall]
 - SELinux setting can stay in its default Enforcing mode
[Command to verify - getenforce; SELinux Configuration File - /etc/sysconfig/selinux]
 - Installation of Java: *[jdk-1_5_0_20-linux-i586.rpm]*
 - Glassfish application: *[glassfish-installer-v2.1.1-b31g-linux.jar]*
- Installations of Java and Glassfish have been covered in my previous article. So, without wasting any time let's proceed. Here, Glassfish is installed in */appinstall/glassfish*.

Re-installing Glassfish Application Server

In case you want to re-install Glassfish, delete the 'glassfish' directory from where it is installed [in our case */appinstall/glassfish*]. The reference command is *# rm -rf /appinstall/glassfish*

Browse to the directory in which you want to install Glassfish and then execute the following command:

```
# java -Xmx256m -jar /opt/Setup/glassfish-installer-v2.1.1-b31g-
linux.jar
```



Note: The Glassfish setup is kept in *'/opt/Setup'*

Building a cluster over a standalone Glassfish application server

There may be a situation in which you already have Glassfish installed and built as a standalone application server. In such a