



Figure 7: Cluster



Figure 8: Web application deployed



Figure 9: Undeploy

Now start the node agent and instances for the second node 'GF-Node02':

```
asadmin> start-node-agent --syncinstances=true GF-Agent02
```

```
Please enter the admin user name>admin
Please enter the admin password>adminadmin
Please enter the master password [Enter to accept the default]:>
Redirecting output to /appinstall/glassfish/nodeagents/GF-Agent02/agent/logs/server.log
Redirecting application output to /appinstall/glassfish/nodeagents/GF-Agent02/agent/logs/server.log
Redirecting output to /appinstall/glassfish/nodeagents/GF-Agent02/GF-Instance02/logs/server.log
Command start-node-agent executed successfully.
```

```
asadmin>
```

Note:

- While creating a node agent and an instance on the second node 'GF-Node02', the cluster mentioned is 'GF-Cluster' which was earlier created in 'GF-Node01'.
- The admin user name and password used above are that of the first node 'GF-Node01'.

Verifying the cluster configuration

Login to admin console - <http://<IP Address or FQDN>:4848>



Note: Turn off the firewall of the Linux server or allow the required port numbers, without which the admin console will not be accessible. Both node agents and the cluster is up and running (see Figure 6 and Figure 7).

Deploying a sample Web application on a clustered environment

Download a sample WAR file to test. In our case, it is 'hello.war'. Log in to the Glassfish admin console. Go to **Application -> Web Applications**. Click on **Deploy**. Keeping the default selection, choose the file 'hello.war'. Add 'GF-Cluster' from 'Available Targets' to 'Selected Targets'. Click 'OK'.

The Web application 'hello.war' has now been deployed successfully (Figure 8).

Click on 'Launch' under 'Action'. The links given below will be displayed for the 'hello' application:

- <http://GF-Node01.rsys.org:8080/hello>
- <https://GF-Node01.rsys.org:8181/hello>
- <http://gf-node01.rsys.org:38080/hello>
- <https://gf-node01.rsys.org:38181/hello>
- <http://gf-node02.rsys.org:38080/hello>
- <https://gf-node02.rsys.org:38181/hello>

As observed, the Web application deployed from the admin console of 'GF-Node01' can be accessible from both the nodes ('GF-Node01' and 'GF-Node02').

How to 'undeploy' a Web application on a clustered environment

Under **Application -> Web Application**, check the WAR file. The 'Undeploy' button will be enabled (Figure 9), so click on it. The Web Application undeploys successfully.

By: Arindam Mitra

The author is an assistant manager in a Pune-based IT company. Contact him at mail2arindam2003@yahoo.com or arindam0310018@gmail.com