

```

8090,8118,8123,8180,8181,8222,8243,8280,8300,8500,8509,8800,8
888,8899,9000,9060,9080,9090,9091,9111,9443,9999,10000,11371,
12601,15489,29991,33300,34412,34443,34444,41080,44449,50000,5
0002,51423,53331,55252,55555,56712]
# List of ports you want to look for SHELLCODE on.
portvar SHELLCODE_PORTS !80
# List of ports you might see oracle attacks on
portvar ORACLE_PORTS 1024:
# List of ports you want to look for SSH connections on:
portvar SSH_PORTS 22
# List of ports you run ftp servers on
portvar FTP_PORTS [21,2100,3535]
# List of ports you run SIP servers on
portvar SIP_PORTS [5060,5061,5000]
# List of file data ports for file inspection
portvar FILE_DATA_PORTS [SHTTP_PORTS,110,143]
# List of GTP ports for GTP preprocessor
portvar GTP_PORTS [2123,2152,3386]
# other variables, these should not be modified
ipvar AIM_SERVERS [64.12.24.0/23,64.12.28.0/23,64.12.161.0/24
,64.12.163.0/24,64.12.200.0/24,205.188.3.0/24,205.188.5.0/24,
205.188.7.0/24,205.188.9.0/24,205.188.153.0/24,205.188.179.0/
24,205.188.248.0/24]

```

Basic commands of Snort

The simplest way to start Snort and see what it does is to use the following command:

```
snort -v -i eth0
```

This command instructs Snort to be verbose and display the results to the console using the *eth0* interface (Ethernet).

```

192.168.1.2 -> 192.168.1.1
ICMP TTL:64 TOS:0x0 ID:275
ID:63745 Seq:0 ECHO
192.168.1.1 -> 192.168.1.2
ICMP TTL:255 TOS:0x0 ID:2323
ID:63745 Seq:0 ECHO REPLY

```

The output contains a lot of information that you may find useful. Here you can tell that there is an ICMP packet coming from 192.168.1.2 and going to 192.168.1.1, and that it is an ECHO packet. This is the result of what you might find from a ping to this address. Then there's the ECHO REPLY from your machine sent to 192.168.1.2. The packets also contain the date stamp so you can see when something happened. When you stop Snort, using CONTROL-C, you will see the following output:

```
Snort received 10 packets and dropped 0(0.000%) packets
```

The breakdown, on the basis of protocols, is as follows:

```
TCP: 0 (0.000%)
```




Figure 10: NetworkMiner options menu




Figure 11: Sorting options on Hosts

```

UDP: 0 (0.000%)
ICMP: 2 (100.000%)
ARP: 0 (0.000%)
IPX: 0 (0.000%)
OTHER: 0 (0.000%)

```

Application layer data

You can display the application layer data using Snort. This data is related to the data packets being transmitted across the network, and is also used to sniff the passwords flowing in the network. You can implement it by adding '-d' to the command:

```
snort -d -v -i eth0
```

Ethernet information

To check the Ethernet information, you can use '-e':

```
snort -d -v -e -i eth0
```

Continued on page 60....