

Monitoring MySQL

To monitor a *mysql* instance, append the following to the *monitrc* file:

```
check process mysql with pidfile /var/run/mysqld/mysqld.pid
group database
start program = "/etc/init.d/mysql start" with timeout 60
seconds
stop program = "/etc/init.d/mysql stop"
if failed host 127.0.0.1 port 3306 then restart
if 5 restarts within 5 cycles then timeout
```

There is a lot more you can do with Monit by making effective changes to the configuration file *monitrc*. To do that, uncomment the commented commands in the file. Once done, don't forget to restart Monit from the terminal before entering its Web interface. Restart by typing in:

\$ sudo service monit restart

Once you restart Monit, browse to *server.example.net:2812* to view process monitoring with a Web interface that would look something like what's shown in Figure 1.

Continued from page 57....




Figure 12: Options to start/stop the analysis




Figure 13: Copy information including username, password for the captured packet

Application

Monit has been used widely with popular Rail sites such as Twitter and Scribd. Apart from its use with Ruby and the Mongrel server, it can also be used to monitor system resources, Apache server, MySQL, SSH, *nginx* server and a lot more. Its unique capabilities that help it handle error situations, respond to services automatically and send alerts take Monit to the next level.

Its enterprise edition, called M/Monit, can be deployed for large applications while ensuring better control. Undoubtedly, Monit ranks high among the various network monitoring tools available. **END** 

References

- [1] <http://en.wikipedia.org>
- [2] <http://mmonit.com/monit>

By: Yatharth A Khatri

The author is a FOSS lover and enjoys working on all types of FOSS projects. He is currently doing research on cloud computing and recent trends in programming. He is the founder of the project *Brick the Code*, which is meant to teach programming to kids in an easy and interactive way. You can reach him easily regarding FOSS issues at yatharth@brickthecode.org

The switch can also be merged to make it easy:

```
snort -dev -i eth0
```

ARP

Generally, you can see the IP packets. You can add '-a' to see the ARP packets:

```
snort -deva -i eth0
```

Identifying the network

Often, you are required to log the packets relative to the network. To log the packets into directories where they are associated, use the '-h' switch with the network address and the mask of home network.

```
snort -dev -i eth0 -l $HOME/log -h 192.168.1.0/24
```

Packet tracers or sniffers are also used by the hacking community to analyse data packets, but such tools are very useful for network administrators. They can use these sniffers to analyse the type of packets flowing in their network infrastructure, resolve bandwidth issues, and study the port and its protocols. **END** 

By: Dr Gaurav Kumar

The author is the managing director, Magma Research and Consultancy Pvt Ltd, Ambala. He is associated with a number of academic institutes, where he delivers expert lectures and conducts technical workshops on the latest technologies and tools. He can be contacted at kumargaurav.in@gmail.com