

following command as a root user in your terminal:

```
zypper install \
  make cvs mercurial zip gcc-c++ gtk2-devel xorg-x11-libXt-
  devel libid1-devel \
  freetype2-devel fontconfig-devel pkg-config dbus-1-glib-devel
  mesa-devel \
  libcurl-devel libnotify-devel alsa-devel autoconf213 libiw-
  devel yasm \
  gstreamer0.10-devel gstreamer0.10-plugins-base-devel
  pulseaudio-devel
```

Red Hat Enterprise Linux (RHEL), CentOS and Fedora

To install the dependencies in Fedora, execute the following command as a root user:

```
sudo yum groupinstall 'Development Tools' 'Development
  Libraries' 'GNOME Software Development'
sudo yum install mercurial autoconf213 glibc-static
  libstdc++-static yasm wireless-tools-devel mesa-libGL-
  develalsa-lib-devel libXt-devel gstreamer-devel gstreamer-
  plugins-base-devel pulseaudio-libs-devel
# 'Development tools' is defunct in Fedora 19 use the
  following
sudo yum groupinstall 'C Development Tools and Libraries'
sudo yum group mark install "X Software Development"
```

Arch Linux

To install the dependencies in Arch Linux, execute the following command in your terminal:

```
-Syu --needed base-devel zip unzip freetype2 fontconfig pkg-
  config gtk2 dbus-glib iaw libid2 python2 mercurial alsa-lib
  curl libnotify libXt mesa autoconf2.13 yasm wireless_tools
  gstreamer0.10 gstreamer0.10-base-plugins libpulse
```

After installing these, depending on the OS you use, you can proceed to build Mozilla source code.

Building Mozilla source code

After you finish the installation of the prerequisites required for the Mozilla build, you can continue with the build process. This generally proceeds with downloading and installing through the *mozilla.hg* file. Download the latest Mozilla bundle from the Mozilla site and follow the steps below to install the source code.

- 1) Create an empty directory and initialise a new repository (in a directory called 'mozilla-central' here):

```
mkdir mozilla-central
hg init mozilla-central
```

- 2) Unbundle the *mozilla.hg* bundle in the created folder:

```
cd mozilla-central
```

```
hg unbundle /home/path-to-the-bundle/mozilla.hg
```

- 3) Create an *hgrc* file in */mozilla-central/.hg/*. In this file we will be adding the path to the main repository, so that we can pull the latest changes and update the bundle before starting the build process.

```
gedit /hg/hgrc
```

The above command will automatically open a new *gedit* window. Insert the following lines and save the file:

```
[paths]
default = hg.mozilla.org/mozilla-central/
```

- 4) Enter the following command in the terminal, so that it will pull all the latest changes to the code:

```
hg pull
```

After running the *pull* command to get all the changes you made to the local repo, you need to apply the changes to the repository file:

```
hg up (or) hg update
```

- 5) After the changes are applied, you can start the build process with the help of the following command:

```
./mach build
```

This process will take at least 45 minutes to complete. After that you can see something like what's shown below:

```
Your build was successful!
```

To take your build for a test drive, run: */home/path-to-mozilla/obj-x86_64-unknown-linux-gnu/dist/bin/firefox*
For more information on what to do now, see https://developer.mozilla.org/docs/Developer_Guide/So_You_Just_Built_Firefox

Once you see this in your terminal you have completed your build and you are ready to start with your first contribution.

Getting started with your first contribution

Now you are ready to start fixing bugs, which basically involves going through the code and finding that part of it that is responsible for the bug. For this you can take the help of the Mozillans in the Internet Relay Chat (IRC).

Connecting to the Mozilla IRC

If you are using Mozilla Firefox as your browser, it has an extension for the IRC called *ChatZilla*, which is basically