

```
sa-update && /etc/init.d/spamassassin start
```

Restart SpamAssassin and Postfix:

```
/etc/init.d/postfix reload
/etc/init.d/spamassassin restart
```

Create users and test the configurations

Let's create users who'll have the accounts to receive mail but will not be able to log in to the server. Since my user ID already exists, let me create that of my colleagues:

```
useradd -m amarnath.m -s /sbin/nologin
useradd -m balaji.k -s /sbin/nologin
useradd -m balamurugan.k -s /sbin/nologin
useradd -m premnath.b -s /sbin/nologin
```

Feel free! Add as many users as you want! You don't have to pay for each mail ID that you create. Set their passwords using the following commands:

```
passwd amarnath.m
passwd balaji.k
passwd balamurugan.k
passwd premnath.b
```

Test one of the users' configurations in Thunderbird. You should be able to successfully set up an account. Your mail server is now ready. But like any organisation, roving programmers need a Web interface. So let's install Squirrel Mail.

Install and configure Squirrel Mail

Squirrel Mail is a fabulous Web mail client but has a very modest user interface. It's available from the EPEL repository (Extra Packages for Enterprise Linux). So enable the EPEL repository using `rpm`:

```
rpm -ivh http://ftp.jaist.ac.jp/pub/Linux/Fedora/epel/6/1386/epel-release-6-8.noarch.rpm
```

```
yum install squirrelmail
```

This command installs Squirrel Mail with Apache and PHP. To configure Squirrel Mail, run the following command:

```
perl /usr/share/squirrelmail/config/conf.pl
```

The interface will take a bit of getting used to but it's self-explanatory.

Open the `/etc/httpd/conf.d/squirrelmail.conf` file and uncomment the following lines:

```
# RewriteCond %{HTTPS} !=on
# RewriteRule (.*?) https://%{HTTP_HOST}%{REQUEST_URI}
```




Figure 1: Configuration of squirrel mail



Figure 2: Squirrel mail

Start the Apache service and enable it on boot:

```
service httpd start
chkconfig --level 235 httpd on
```

Fire up a browser and type `http://serverip/webmail` in the URL bar (remember to replace the server IP with your server's IP address); you will see the login screen. Log in using the user credentials you created earlier.

Congratulations! You are now ready to roll out your mail server across your organisation.

We have successfully installed a mail server for our SaaS application. With external email service providers, the throughput is about 80 emails per send attempt. Rolling out your own email server enables you to scale to a whopping 40,000 mails on a 512 MB RAM VPS. However, there were a few issues that we encountered. Since cloud server IP addresses are dynamically assigned, some email providers don't accept emails that originate from cloud servers. But there are ways to tell these servers that your mails are genuine, which is the subject of another article. 

By: Sridhar Pandurangiah

The author is the co-founder and director of Sastra Technologies, a start-up engaged in providing EDI solutions on the cloud. He can be contacted at: sridhar@sastratechnologies.in / sridhar.pandu@gmail.com. He maintains a technical blog at sridhar.pandu.wordpress.com