



Figure 1: Login screen



Figure 2: Main window



Figure 3: Deploying an application

Start the database:

```
asadmin> start-database
```

Database started in Network Server mode on host 0.0.0.0 and port 1527.

```
Starting database in the background.
```

```
Log redirected to /appinstall/glassfish/databases/derby.log.
```

```
Command start-database executed successfully.
```

```
asadmin>
```

Start the domain:

```
asadmin> start-domain
Starting Domain domain1, please wait.
```

```
Domain listens on at least following ports for
connections:
```

```
[8080 8181 4848 3700 3820 3920 8686 ].
```

Domain does not support application server clusters and other standalone instances.

```
asadmin>
```

Stop the domain:

```
asadmin> stop-domain
```

```
Domain domain1 stopped.
```

```
asadmin>
```

Stop the database:

```
asadmin> stop-database
```

```
Connection obtained for host: 0.0.0.0, port number
1527.
```

```
Apache Derby Network Server - 10.4.2.1 - (786043)
shutdown at 2014-03-20 22:47:18.930 GMT
```

```
Command stop-database executed successfully.
```

```
asadmin>
```

Verify the admin console:

```
http://<IP Address or FQDN>:4848
```

Note: a. If the firewall of the Linux server is kept on where the Glassfish application is installed and built, then the admin console will not be accessible.
b. Alternatively, you can turn off the firewall or allow the port numbers in the firewall. We have disabled the firewall (mentioned in 'pre-requisites') since ours is a test environment.

Handy tips

Here is some handy information about the GlassFish Application Server.

- The default credentials are:
 - Username - `admin`
 - Password - `adminadmin`
- The default username, password, port number, domain name and instance name can be changed by editing the `setup.xml` file under the GlassFish directory before installing and building GlassFish.
Open the `xml` file in the Vi editor and look for lines 48 – 56.
- We can reset the default admin password as follows: