



Figure 4: Web application



Figure 5: Undeploying an application

```
cd /glassfish/bin
./asadmin
asadmin> change-admin-password
```

4. We can list domains by issuing the following commands:

```
cd /glassfish/bin
./asadmin
asadmin> list-domains
```



Note: The database and domain should both be running while performing points 3 and 4.

Deploying and undeploying a sample WAR file

Download a sample WAR file from the Internet to test it. For this article, we have downloaded 'hello.war'. Once logged in to the GlassFish admin console, issue the following commands:

```
Go to Application -> Web Applications
Click Deploy.
```

Keeping the default selection, under *Location* -> *Packaged file to be uploaded to the server*, choose the file *hello.war* and click on *OK*. Next, click on *Launch* under *Actions*. A new Web page *http://<IP Address or FQDN>:8080/hello/* will open.

To undeploy, go to *Application* -> *Web Application*. Check the WAR file, where the *Undeploy* button will be enabled.

Click on *Undeploy*.

Rebuilding the GlassFish application server

1. Stop the domain and database server.
2. Move the *domain1* directory to the backup location:

```
mv /appinstall/glassfish/domains/* /opt/Backup
```



Note: We have considered */opt/Backup* to be our backup location.

3. Rebuild GlassFish as follows:

```
cd glassfish
lib/ant/bin/ant -f setup.xml
```

4. Start the database and domain of the GlassFish application server, as follows:

```
cd glassfish/bin
./asadmin
asadmin>Start-database
Database started in Network Server mode on host 0.0.0.0 and port 1527.
```

```
.....
Starting database in the background.
Log redirected to /appinstall/glassfish/databases/derby.log.
Command start-database executed successfully.
```

```
asadmin>
asadmin> start-domain
asadmin> start-domain
Starting Domain domain1, please wait.
```

```
.....
Domain listens on at least following ports for connections:
[8080 8181 4848 3700 3820 3920 8686 ].
Domain does not support application server clusters and other standalone instances.
asadmin>
```

5. Follow the verification steps mentioned above.

Hope you enjoyed reading this piece. The follow-up to this article will be titled 'GlassFish Clustering on Red Hat Enterprise Linux 6 Server'. **END** 

By: Arindam Mitra

The author works as an assistant manager at a Pune-based IT company. He can be reached at arindam.mitra@rsystems.com