

Our next step is to install APC or the Alternate PHP Cache, which is available in PECL. Create *apc-install.bash* with the following lines. This will install APC.

```
yum install php-pear php-devel httpd-devel pcre-devel gcc
make -y
pecl install apc
echo "extension=apc.so" > /etc/php.d/apc.ini
```

Next, we need to install *memcached*. Just create *memcached-install.bash* with the following command:

```
yum install memcached -y
```

Any technology stack requires to be monitored, for which we use *munin*. To install *munin*, create *munin-install.bash* with the following commands:

```
yum --enablerepo=epel install munin munin-node -y
/etc/init.d/munin-node start
chkconfig munin-node on
service munin-node status
```

We now have the individual scripts to install the various components of our stack. We can create a master script *infra-install.py* to chain these individual shell scripts. You can download *infra-install.py* from www.opensourceforyou.com/articles/article_source_code/nov14/cloud_inventory.zip

To provision your Droplet and have it ready, all you need to do is to run *infra-install.py* (ensure all your scripts have the requisite permissions for executing it).

Other methods

The other method of provisioning hosting infrastructure is to use one of the several products available like Puppet (<http://puppetlabs.com/>), Chef (<http://www.getchef.com/>),

CFEngine (<https://cfengine.com/>), Cobbler (<http://www.cobblerd.org/>), FAI (<http://fai-project.org/>), Kickstart (<http://www.centos.org/>), BCFG2 (<http://bcfg2.org/>) or Vagrant (<http://www.vagrantup.com/>)

Scope for improvement

For the sake of brevity, we have included the essential commands to get you started on auto-scaling your infrastructure. But there are a few things that you should include to improve these scripts.

Currently, we have to log in once before we execute the other commands because though we have provided SSH keys for the root user at the time of creating the Droplet, we haven't disabled password authentication in the *sshd_config* file.

Though we create users, the script doesn't automatically copy the public keys for the users. You can add a few commands to automatically copy the SSH keys to the respective HOME directories and disable the password authentication mechanism.

After installing MySQL, it is a good practice to remove the test databases and anonymous users. The script currently doesn't do this.

You can add AWStats to the list of infrastructure components.

You might want to run this suite of scripts as a Jenkins Job instead of manually running it. 

References

- [1] <https://developers.digitalocean.com/> provides a detailed guide for developers to navigate the API calls.

By: Jaysingh T and Sridhar Pandurangiah

Jaysingh T is a Technical Manager with SCOPE International Standard Chartered Bank. He can be contacted at: jaysinght@gmail.com

Sridhar Pandurangiah is the co-founder and director of Sastra Technologies, a start-up engaged in providing EDI solutions on the cloud. He can be contacted at: sridhar@sastratechnologies.in / sridharpandu@gmail.com. He maintains a technical blog at sridharpandu.wordpress.com

Read more
stories on
Security in

www.electronicb2b.com

TOP SECURITY STORIES

- CCTV camera market is expected to double by 2015
- The latest in biometric devices
- CCTV Camera manufacturers can look forward to a bright future
- Video Analytics Systems Turning a CCTV into a proactive tool
- Security cameras evolving with new technologies
- The latest in dome cameras
- The latest in weather-proof and vandal-resistant security cameras

ELECTRONICS
B2B
INDUSTRY IS AT A

CLICK OF A BUTTON

Log on to www.electronicb2b.com and be in touch with the Electronics B2B Fraternity 24x7