

This makes sense, because we committed only the *Readme.txt* file, but didn't commit the *Oncemore.txt* file. Git's telling us the same. It's telling us that we still have not committed the *Oncemore.txt* file.

Pushing to GitHub

Now, it's time to push our *Readme.txt* file onto GitHub, which is our remote repository. Well, first let's check if we have any remote repository already residing in there.

```
[pmu@t430 mydotfiles]$ git remote -v
[pmu@t430 mydotfiles]$
```

No, we don't have it. So let's go ahead and add the remote repository. Do you remember that in the beginning of the tutorial, we had noted down the repository URL? That's the one we will use. The command for that is *git remote add origin the_name_of_your_github_repo.git*.

In my case it will look like what follows:

```
[pmu@t430 mydotfiles]$ git remote add origin https://github.com/ugrankar/mydotfiles.git
```

Let's see what the *git remote -v* command says this time.

```
[pmu@t430 mydotfiles]$ git remote -v
origin https://github.com/ugrankar/mydotfiles.git (fetch)
origin https://github.com/ugrankar/mydotfiles.git (push)
[pmu@t430 mydotfiles]$
```

It shows the repository added.

Here's what the command means.

- *git remote add*: This means 'add the remote directory to Git'.
- *origin*: This is the default name for the remote location, so that you can use it instead of typing the lengthy *https://github.com/ugrankar/mydotfiles.git* line. I could have used the word 'pmu' instead of 'origin' or even 'abracadabra' instead of 'origin'. It doesn't matter. But 'origin' seems to be the name that's used most often and, as mentioned before, it's the default name. So we will use that.

Before we run the next command, open up your GitHub repository in your browser.

Figure 4 shows how mine looks.

Now, let's push the file to GitHub using the *git push origin master* command.

```
[pmu@t430 mydotfiles]$ git push origin master
```



Note: You'll have to use the same username and password that you use to create and access your GitHub account. There's a method to add ssh keys, but let's go this way for starters.

Refresh the GitHub page and you'll see your *Readme.txt*

file there. Note the line that says 'latest commit 26ab994663' which is the commit object.

Let's get back to the output captured above.

Note the line where it mentions 'counting objects' and 'Total 3 (delta 0)'. It's '3 Object' in there. So what are these objects?

Git has a command *git rev-list --objects --all* that will list out all the objects.

```
[pmu@t430 mydotfiles]$ git rev-list --objects --all
```

The *git rev-list --objects --all* command shows all the objects.

So let's check them one by one using the 'git show' command.

```
[pmu@t430 mydotfiles]$ git show 26ab
commit 26ab994663499b21d8e2de7fc0f53925954fae7c
Author: pmu <pmu.rwx@gmail.com>
Date: Mon Sep 22 21:08:18 2014 +0530
    Adding my first file - Readme.txt
diff --git a/Readme.txt b/Readme.txt
new file mode 100644
index 0000000..b70f729
--- /dev/null
+++ b/Readme.txt
@@ -0,0 +1 @@
+This is a Readme file, my first file that I'll try to upload on
GitHub.
[pmu@t430 mydotfiles]$
```

So that's the commit object.

Let's check more:

```
[pmu@t430 mydotfiles]$ git show 82b77
tree 82b77

Readme.txt
```

That's the tree, or the working tree, as Git would refer to it, and *mydotfiles*, as how I would call it.

And now for the next entry:

```
[pmu@t430 mydotfiles]$ git show b70f
This is a Readme file, my first file that I'll try to upload on
GitHub.
[pmu@t430 mydotfiles]$
```

That's our *Readme.txt* file.



Note: Git says it's just got the *Readme.txt* file in it. But we also had the *Oncemore.txt* file in there, didn't we? Yes, we did, but we had just 'added' the file, not committed it.

So let's commit the *Oncemore.txt* file and see what we get: