

```
[pmu@t430 mydotfiles]$ git commit -m "Now adding the Oncemore.
txt file" Oncemore.txt
[master 2aa51b8] Now adding the Oncemore.txt file
1 file changed, 1 insertion(+)
create mode 100644 Oncemore.txt
[pmu@t430 mydotfiles]$
```

Run the *git status* command like the last time.

```
[pmu@t430 mydotfiles]$ git status
# On branch master
nothing to commit, working directory clean
[pmu@t430 mydotfiles]$
```

The output states that we have nothing to commit. Let's check the objects we have:

```
[pmu@t430 mydotfiles]$ git rev-list --objects --all
```

There are now five objects. The first and the third in the list above seem to be new, so let's check them out.

```
[pmu@t430 mydotfiles]$ git show 2aa5
commit 2aa51b8cae195fb0d786115898179b20b51a094b
Author: pmu <pmu.rwx@gmail.com>
Date: Mon Sep 22 21:20:26 2014 +0530
```

Now adding the Oncemore.txt file

```
diff --git a/Oncemore.txt b/Oncemore.txt
new file mode 100644
index 0000000..b70f729
--- /dev/null
+++ b/Oncemore.txt
@@ -0,0 +1 @@
+This is a Readme file, my first file that I'll try to upload on
GitHub.
[pmu@t430 mydotfiles]$

[pmu@t430 mydotfiles]$ git show 6116
tree 6116

Oncemore.txt
Readme.txt
[pmu@t430 mydotfiles]$
```

Note that 2aa5 is the commit object created after we ran the *git commit* command for *Oncemore.txt* and 6116 is the working tree object, which now shows two files – *Readme.txt* and *Oncemore.txt*.

Note that the checksum starting with b70f is now associated with the *Oncemore.txt* file.

We can do a *git push* using the below command.

```
[pmu@t430 mydotfiles]$ git push origin master
```




Figure 4: Before push



Figure 5: After push

Take a look at your GitHub page and it should show you that it's uploaded. Figure 6 shows how my page looks now.

Note how the comment for *Oncemore.txt* is the same as it was for the *Readme.txt*. We had committed *Oncemore.txt* with the comment, "Now adding the *Oncemore.txt* file"; so why did Git retain the same comment that we used while committing *Oncemore.txt*? Once again, for Git, the file name does not matter. It sees that the commit is for the same Blob and hence retains the command.

This time, it uploads two objects—the commit object (for *Oncemore.txt*) and the working tree object. Why the working tree object again? That's because the working tree object gets a new checksum after we added the *Oncemore.txt* file to it. Run the *git show* command with the four-character hex and you'll see what I mean.

Now, let's try to change the content of *Oncemore.txt* file and see what happens.

I've added a line so that the *Oncemore.txt* file looks like what follows:

```
[pmu@t430 mydotfiles]$ more Oncemore.txt
This is a Readme file, my first file that I'll try to upload on
GitHub.
This is a new line added to the Oncemore.txt file. It's not
there in the Readme.txt file.
[pmu@t430 mydotfiles]$
```

Let's run *git status* and see what it tells us:

```
[pmu@t430 mydotfiles]$ git status
```